

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7705)

Set a stone, 15x10x6 ins., 10" in the ground for 1/4 sec. cor. marked 1/4 on W. face, from which

A Fir 6" dia., bears N.21°E., 22 lks. dist. mkd. 1/4 S BT.

A Fir 18" dia., bears N.81°W., 31 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones crew - April 4, 1966 - C.S. File 52/63-88

Found - No trace of 6" Fir N.21°E., 14.5 ft.
18" Fir now 34", S.81°W., 20.4 ft., opened for scribing "4".

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W
1/4 S 35 | S 36
1966

New BT - 20" D.Fir N.7°W., 75.2 ft. scribed 1/4 S35 CS BT.

Reblazed and rescribed:

34" D.Fir S.81°W., 20.4 ft. scribed 1/4 S35 CS BT.

This corner lies in cut unit about 600 ft. East of logging road.

Survey by Glenn S. Baughman - For: U.S. Forest Service - Nov. 1979 - C.S. File 58/176-17

Found - 1" I.P., firmly set, 15" above the ground with a 1966 county brass cap properly marked.

Orig. 34" D.Fir snag with scribe marks "1/4 S35 CS BT" visible, bears S.81°W., 20.4 ft.

A 24" D.Fir with scribe marks "1/4 S35 CS BT" visible bears N.7°W., 75.2 ft. (1966 BT)

New BT - 6" D.Fir bears S.38°E., 32.5 ft. mkd. "1/4 S36 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

Fd. OK, March 1991 - M 111-67

DCSO-GIS Corner visitation - 2/20/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 1.25" IP/BC

Comment - ok