

PRIMARY CORNER DESCRIPTION Sec Cor for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page 7705-06)

Set a stone 12x12x10 ins., 8" in the ground, for cor. to secs. 25, 26, 35 and 36, marked with 1 notch on E. and S. edges; from which

A Fir 28" dia., bears N.66°E., 47½ lks. dist. mkd. T31S R3W S25 BT.

A Fir 12" dia., bears S.59½°E., 43 lks. dist. mkd. T31S R3W S36 BT.

A Fir 9" dia., bears S.6°W., 17 3/4 lks. dist. mkd. T31S R3W S35 BT.

A Fir 8" dia., bears N.37½°W., 35½ lks. dist. mkd. T31S R3W S26 BT.

George Wenderoth - (Date ?) - C.S. File 45/230

1" Iron pipe, from which
18" Fir N.38°30'W., 23.4 ft.
28" Fir N.59°20'E., 31.3 ft.
12" Fir S.2°45'W., 10.5 ft.
30" Fir S.75°50'E., 24.0 ft.

Fd. OK, Dec. 1965 by DCSO, John Powell - C.S. File 52/63-39

Douglas Co. Surveyors Office - John M. Powell, Frank Jones crew - April 4, 1966 - C.S. File 52/63-89

Found - 18" Fir now 15", N.38½°W., 23.4 ft. scribe visible "T31".

30" Fir now stump, S.75°50'E., 24.0 ft. scribe visible "S36 CS BT"

No trace of 28" Fir N.59°20'E., 31.3 ft. (Road)

No trace of 12" Fir S.2 3/4°W., 10.5 ft.

No trace of Iron pipe as recorded.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

S 26 | S 25

S 35 | S 36

1966

New BTs- 26" D.Fir N.26°E., 30.0 ft. scribed T31S R3W S25 CS BT.

15" D.Fir S.68°W., 25.6 ft. scribed T31S R3W S35 CS BT.

This corner lies on edge of old, logging road.

(Cont. Next Page)

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Survey by Glenn S. Baughman, LS #536 - For: U.S. Forest Service - Nov. 1979 - C.S. File 58/176-015A

Found - A 1" I.P., firmly set, projecting 14" above the ground with a 2½" brass cap, 1966, properly mkd. Orig. D.Fir 19", with scribe marks visible on a partially healed blaze, bears N.37½°W., 23.4 ft. to face.
A D.Fir 30", rotted stump, bears S.75°50'E., 24.0 ft. mkd. by Wenderoth.
28" D.Fir with scribe marks visible on a partially healed blaze bears N.26°E., 30.0 ft. Powell BT.
18" D.Fir with scribe marks visible on a partially healed blaze, bears S.68°W., 25.6 ft. Powell BT.
New BT - 16" Cedar bears S.56°E., 106.4 ft. mkd. "T31S R3W S36 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

Found - 2½" brass cap (properly mkd) 1966
29.5" fir with healed face & tag dated 4/66 N.26°E., 30.0' to nail side center
Rotten stump 3' tall & tag dated 11/86 S.76°E., 24.0'
25" cedar with healed face & tag dated 7/25/79 S.56°E., 106.4' to nail side center
20" fir with healed face & tag dated 4/66 S.68°W., 25.6'
25" fir with healed face & tag dated 7/23/79 N.37½°W., 23.4' to nail side center.