

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7707)

-----  
Set a stone 14x10x10 ins., 10" in the ground for 1/4 sec. cor. marked 1/4 on W. face; from which

A Fir 12" dia., bears S.78°W., 22 lks. dist. mkd. 1/4 S BT.

A Fir 11" dia., bears S.12 1/4°E., 19 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 52/63-96

-----  
Found - Stone at 1/4 corner "1/4" on West face.

12" Fir now rotten stump, S.78°W., 14.5 ft.

11" Fir now 14", S.12 1/2°E., 12.5 ft. Has been opened for scribe. Face rotten but faint scribe marks visible.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S26 | S 25

1966

New BTs- 13" Hemlock N.40°E., 23.0 ft. scribed 1/4 S25 CS BT.

25" D.Fir N.31°W., 6.2 ft. scribed 1/4 S26 CS BT.

Kris DeGroot - For Roseburg Resources Co. - 5/2010 - M157-24

-----  
Lat: 42°50'58.371613"N Long: 123°00'46.738768"W

Found - 1 1/4" iron post by Powell, DCSO deputy surveyor in 1966, per C.S. file No. 52/63, firmly set, projecting 15" above the ground with a 2 1/2" brass cap (properly mkd.)

From which an original bearing tree by W. Bushey in 1893:

A 16" D.Fir stob, 12 ft. Tall, bears S.12 3/4°E., 12.2 ft with a healed blaze. (Rec. S.12 1/2°E., 12.5 ft)

And bearing trees by J. Powell in 1966:

A 34" D.Fir bears N.32 1/2°W., 5.8 ft with a healed blaze. (Rec. N.31°W., 6.2 ft) **CORRECTED 5/4/2015**

A root hole with an uprooted 16" hemlock alongside bears N.40°E., 23.0 ft.

New BT - A 9" hemlock bears N.84 3/4°E., 32.9 ft scribed "1/4 S25 BT"

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

-----  
Found - 2 1/2" brass cap (properly mkd) 1966

9" hemlock with visible scribes & tag dated 3/10 N.84 3/4°E., 32.9' to nail side center. cont.

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

15.5" snag 20' tall with visible scribes & tag dated  
7/56 S.12½°E., 13.9'  
34.5" fir with healed face & tags dated 1966 & 1979  
N.31°W., 6.2'