

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7710)

Set a post, 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23 and 24, marked T31S S13 on NE.; R3W S24 on SE.; S23 on SW.; and S14 on NW. faces, with 1 notch on E. and 3 notches on S. edges, from which

A Fir 12" dia., bears N.65¼°E., 28 lks. dist. mkd. T31S R3W S13 BT.

A Fir 12" dia., bears S.58½°E., 19 lks. dist. mkd. T31S R3W S24 BT.

A Fir 24" dia., bears S.31½°W., 56½ lks. dist. mkd. T31S R3W S23 BT.

A Laurel 12" dia., bears N.66 3/4°W., 37 lks. dist. mkd. T31S R3W S14 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - Dec. 1959 - C.S. 42/392-50

Determined by O.B.T.s:

15" Laurel N.67°W., 24.4 ft., I rescribed S14 BT.

30" Fir S.31°W., 37.0 ft.

16" Fir S.58°E., 12.5 ft.

20" Fir N.65°E., 18.5 ft.

At corner point, Set 1/2" x 30" Iron pipe, from which

11" Fir N.8°E., 45.7 ft. "S13 T31S BT".

14" Laurel N.40°W., 35.2 ft. "S14 T31S R3W BT".

4" Cedar S.42°W., 18.2 ft. "S23 BT".

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

Found - 3/4" iron pipe

30" fir with healed face and tag dated 7/55, N.70°E., 18.3'

36" fir with healed face and tag dated 1959 S.31°W., 37.0'

20" madrone with healed face set tag dated 10/14 N.62°W., 25.2' feet to nail side

New BT - 27" Fir, (mkd: T31S R3W S24 BT) set tag dated 10/14 S.55°E., 11.9' to nail side center.

Fd. BC, 4 BTs 9/2015 - By Ron Quimby, C.S. 65/89-27 - Area Burnt 8/2015 - Placed 60D spike in base @ side center of trees