

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7712)

A Fir tree, 7" dia., which I mark ¼ S on W. face, for ¼ sec. cor., from which

A Fir 9" dia., bears N.56°E., 24½ lks. mkd. ¼ S BT.

A Fir 8" dia., bears S.83 ¾°W., 13½ lks. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Oct. 7, 1959 - C.S. File 42/392-31

Determined by O.B.Ts:

14" Fir N.56°E., 15.8 ft., found scribe.

12" Fir N.74°W., 8.6 ft.

At corner point, found 12" Fir mkd. on West face and Set ¾" x 30" iron pipe, from which

36" Cedar bears S.13°E., 21.5 ft. mkd. ¼ S13 R3W BT.

12" Fir bears S.74°E., 24.0 ft. mkd. on bark, ¼ S13 BT.

Corner lies on top of side ridge.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-20

Found - ¾" Iron pipe at base of corner tree.

14" Fir N.56°E., 15.8 ft., Orig. BT, opened for scribe.

36" Cedar S.13°E., 21.5 ft. scribe visible "¼ S13 R3W BT"

12" Fir S.74°E., 24.0 ft., bark scribed.

12" Fir, down, N.74°W., 8.6 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

¼ S 14 | S 13

1965

New BT - 12" Fir S.72°W., 37.6 ft. scribed ¼ S14 CS BT.

As noted, corner lies on top of side ridge.

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

Found - 2½" brass cap (properly mkd) iron pipe set in base of original tree tag on tree dated 1959,

BT references are to reference monument -

17" Fir original BT with healed face and tag dated 11/41 N.56°E., - 15.8'

19" fir with healed face and BLM tag dated 1959 S.74°E., 24.0'

continued next page

