

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page 7712-13)

-----  
Set Fir post, 5 ft. long, 4" sq., 24" in the ground, for cor. to secs. 11, 12, 13 and 14, marked T31S S12 on NE.; R3W S13 on SE.; S14 on SW.; and S11 on NW. faces, with 1 notch on E. and 4 notches on S. edges, from which

A Fir 14" dia., bears N.8°E., 120½ lks. dist. mkd. T31S R3W S12 BT.

A Y.Pine 34" dia., bears S.77¼°E., 186 lks. dist. mkd. T31S R3W S13 BT.

A Fir 12" dia., bears S.58½°W., 79 lks. dist. mkd. T31S R3W S14 BT.

A Fir 16" dia., bears N.84½°W., 89½ lks. dist. mkd. T31S R3W S11 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Aug. 11, 1959 - C.S. File 42/392-24

-----  
Determined by O.B.T.s:

30" Fir N.8°E., 79.3 ft.

26" Fir N.86°W., 59.3 ft.

26" Fir S.55°W., 52.0 ft.

At corner point, Set 3/4" x 30" Iron pipe, from which

12" Laurel bears N.89°E., 17.3 ft. mkd. S12 T31S R3W BT.

5" Fir bears N.13°E., 4.0 ft. mkd. S12 BT.

6" Fir bears N.49°W., 4.0 ft. mkd. S11 BT.

6" Laurel bears S.21°W., 10.9 ft. mkd. S14 T31S R3W BT.

6" Fir bears S.18°E., 12.6 ft. mkd. S13 X BT.

Corner lies on top of main ridge.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-18

-----  
Found - No trace of Iron pipe at corner.

12" now 13" Laurel, N.89°E., 17.3 ft., scribing visible.

6" now 8", Fir S.18°E., 12.6 ft., scribing visible.

No trace of NE. or NW. or SW. BTs.

26" now 30" Fir, (orig BT) N.86°W., 59.3 ft., shows face.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

S 11 | S 12

S 14 | S 13

1965

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 8" Laurel S.61°W., 20.6 ft. scribed T31S R3W S14 CS  
BT.

This corner falls in fire trail, therefore, destroying some  
of the bearing trees.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 8/2015 - C.S.  
File 65/89-31

-----  
Found - DCS0 brass cap  
14" Laurel N.89°E., 17.3 ft. good scar.  
36" Fir snag, N.86°W., 59.3 ft. good scar.  
Both trees burnt.

New - 5/8" I.Rod N.52°W., 30.0 ft.  
5/8" I.Rod S.36°W., 15.0 ft.  
5/8" I.Rod S.35°E., 25.0 ft.  
All I.Rods have alum. cap stamped ie engineering  
with alum post.

Note - Corner is approx. 300' east of road near ridge top.  
Area badly burnt 8/2015  
Compass decl. 15½°E.