

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7715)

Set a stone 18x12x4 ins., 12" in the ground, for 1/4 sec. cor. marked 1/4 on W. face; from which
A Laurel 10" dia., bears S.61 1/4°W., 32 lks. mkd. 1/4 S BT.
A Fir 36" dia., bears S.36 1/2°E, 56 lks. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R. G. Boyd - June 29, 1959 - C.S. File 42/392-21

Determined by O.B.T.s:
40" Fir bears S.37°E., 38.0 ft.
14" Laurel bears S.61°W., 22.0 ft., I rescribed 1/4 S12 BT.
At corner point, found stone and Set 1/2" x 24" Iron rod, from which
24" Laurel bears N.36°E., 40.8 ft. mkd. 1/4 S12 T31S BT.
14" Laurel bears N.3°W., 43.5 ft. mkd. 1/4 S11 BT.
30" Fir bears S. (?) W. 45.0 ft. mkd. 1/4 S12 R3W BT.
30" Fir bears S.20°W., 21.7 ft. mkd. 1/4 S11 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-17

Found - 1/2" Iron rod and stone at 1/4 corner.
24" Laurel N.36°E., 40.8 ft., scribe visible.
14" now 15" Laurel, N.3°W., 43.5 ft.
30" D.Fir S.20°W., 21.7ft., bark scribed.
30" D.Fir S.(?) W., 45.0 ft., bark scribed. (Find bearing to be S.81°W.)
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
1/4 S11 | S12
1965
New BTs- 30" D.Fir S.20°W., 21.7 ft. scribed 1/4 S11 CS BT.
12" Laurel S.60°W., 21.2 ft. scribed 1/4 S11 CS BT.
(This tree was here but not recorded, and bark scribed.)

Ron Quimby - For: Roseburg Resources Co - Jan. 2015 - M166-29

Found - Brass cap per 1965 Douglas Co. Surveyor's Office renewal.
33" Fir S.84°W., 42.7' bark scribe visible.
33" Fir S.22°W., 21.4' bark scribe visible.
14" Madrone S.61°W., 20.8' healed scar.
17" Madrone N.3°W., 43.6' healed scar.
26" Madrone N.34°E., 40.7' healed scar. cont.

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

39" Fir S.36°E., 36.2' healed scar.
New BT - 13" Fir N.50°W., 25.4' scribed "¼ S6 BT"