

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7717)

Set a stone, 18x12x6 ins., 12" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which

A Laurel 18" dia., bears N.53½°E., 20 lks. mkd. ¼ S BT.
A Y.Pine 26" dia., bears S.61½°W., 34¾ lks. mkd. ¼ S BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd; Vern Killian - May 4, 1959 - C.S. File 42/392-18

Determined by O.B.T.s:

30" Pine snag bears S.61°W., 22.8 ft., found scribe.
At corner point, Set 1/2" x 30" Iron pipe, from which
9" Laurel bears S.85°E., 25.0 ft. mkd. ¼ S1 T31S R3W BT.
12" Laurel bears N.21°E., 40.5 ft. mkd. ¼ S1 T31S R3W BT.
20" Laurel bears N.13°W., 42.0 ft. mkd. ¼ S2 T31S R3W BT.
9" Laurel bears S.81°W., 8.0 ft mkd. ¼ S2 T31S R3W W.M. BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-23

Found - 1/2" Iron pipe at corner.
30" Pine snag S.61°W., 22.8 ft., is gone.
9" now 13" Laurel S.85°E., 25.0 ft. scribed ¼ S1 T31S R3W BT.
12" now 13" Laurel N.21°E., 40.5 ft., bark scribed.
20" now 21" Laurel N.13°W., 42.0 ft., bark scribed.
9" now 14" Laurel S.81°W., 8.0 ft., barks scribed.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
¼ S 2 | S 1
1965

New BT - 5" Fir N.61°W., 10.4 ft. scribed ¼ S2 CS BT.
Rescribe-21" Laurel N.13°W., 42.0 ft. scribed ¼ S2 CS BT.

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I

Found - 2½" brass cap (properly mkd)
16" dead madrone with healed face and tag dated 1959
S.81°W., 8.0'
9.5" Fir with healed face and tag dated 1965
N.61°W., 10.5'

New BT - 7.8" fir (mkd: "X" BT) set tag dated 10/28/2013
S.32°E., 13.0' to nail side center.

continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Fd. BC & 5 BTs by R Quimby; Area badly burnt 8/2015 - Hand
held Lat & Long: N. 42°54.496 W.123°00.796