

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7706)

-----  
Set a stone 12x12x12 ins., 8" in the ground, for 1/4 sec. cor. marked 1/4 on N. face, from which

A Fir 11" dia., bears N.29 1/2°W., 33 lks. mkd. 1/4 S BT.

A Hemlock 6" dia., bears S.10 1/2°W., 12 lks. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 52/63-97

-----  
Found - 12x12x12" stone mkd. 1/4 on North face.  
6" Hemlock now 8", S.10 1/2°W., 7.9 ft., scribe visible "1/4S".

No trace of 11" Fir, N.29 1/2°W., 21.1 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S 25

S 36

1966

New BT - 7" Yew Wood N.19°W., 37.2 ft. scribed 1/4 S25 CS BT.  
This corner lies West of creek, 22.0 ft.

Fd. OK, March 1991 - M 111-67

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

-----  
Found - 2 1/2" brass cap (properly mkd) 1966  
18.5" hemlock with blazed face & tag dated 10/10/13  
S.10 1/2°W., 8.5' to nail side.

9" yew with visible scribes and tag dated 4/66  
N.19°W., 37.2'

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 3/2018 - C.S. File 65/101-26

-----  
Found - DCSO brass cap (properly mkd)  
Down 19" Hemlock S.10 1/2°W., 8.5 ft.  
Dead 10" Yew N.19°W., 37.2 ft. vis. scribed.  
6' T.Post 6' East.

New - 10" hemlock N.53°E., 16.9 ft. scribed 1/4 S25 BT.

10" Hemlock S.72°E., 38.2 ft. scribed 1/4 S36 BT.

8" W.Fir S.55°E., 15.6 ft. scribed 1/4 S36 BT.

12" Hemlock N.2°W., 26.7 ft. scribed 1/4 S25 BT.

Note - Compass decl. 15 1/2°E.