

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7709)

Set a stone 14x10x10 ins., 9" in the ground, for ¼ sec. cor. marked ¼ on N. face; from which
A Fir 9" dia., bears N.54°E., 68 lks. dist. mkd. ¼ S BT.
A Fir 12" dia., bears S.41 3/4°W., 15 lks. dist. mkd. ¼ S BT.

Survey by Richard L. Templin, Jr. - Sept. 1958 - C.S. File 42/390

Found - Stone mkd. ¼ on North face.
48" Fir S.27°E., 15 lks., dead and down.
30" Fir N.54°E., 66 lks., blaze healed.
Scribed- 10" Fir S.18°W., 35.4 ft. mkd. ¼ S25 RE3024 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - June 28, 1961 - C.S. File 42/392-72

Determined by O.B.T.s:
35" Fir N.54°E., 44.9 ft.
48" Fir uproot, S.27°E., 9.9 ft.
All other BTs gone.
At corner point, found stone and Set 1¼" x 30" Iron pipe, from which
14" Fir bears N.6°E., 19.0 ft. mkd. ¼ S24 BT.
14" Fir bears N.52°E., 23.5 ft. mkd. ¼ S24 BT.
5" Fir bears S.47°E., 20.2 ft. mkd. ¼ S BT.
4" Fir bears S.19°E., 18.4 ft. mkd. ¼ S BT.

Survey by William J. Ruppert, LS #866 - For: U.S. Forest Service - April 1980 - C.S. File 58/143 (n) and M 79-43

Found - 1¼" Iron pipe with 11" x 7" x 9" stone next with no apparent markings.
18" broken top D.Fir snag, bears N.01°42'E., 18.7 ft. with good scars.
20" D.Fir bears N.51°48'E., 22.1 ft. with scars.
44" D.Fir bears N.54°E., 43.5 ft. previously opened and rehealed.
12" D.Fir bears S.48°20'E., 18.9 ft. with good scar.
12" D.Fir bears S.19°51'E., 18.2 ft. with good scar.
Replaced iron pipe with 2" x 30" alum. pipe with 2½" alum. cap mkd. "T31S R3W ¼ S24 and S25 PLS 866 1980". Buried 1¼" Iron pipe along side of alum. pipe.

continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

James Klein - Keith Primm - Douglas Popham - For:
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I &
M171-2 A-D

Found - 2½" aluminum cap stamped PLS 866, 1980
29" fir with healed face & tag dated 4/80 N.51°48'E.
24.0' to nail side center.
49" fir with healed face & tag dated 4/80 N.54°E.,
43.5' to nail side center
17" fir with healed face & tag dated 4/80
S.48°20'E., 19.5' to nail side center.
19" Fir with healed face & tag dated 4/80
S.19°51'E., 18.45' to nail side center