

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7711)

-----  
Set a stone 14x10x10 ins., 9" in the ground, for 1/4 sec. cor. marked 1/4 on N. face; from which

A Laurel 14" dia., bears S.73°E., 25 lks. mkd. 1/4 S BT.

A Fir 30" dia., bears N.29°E., 63 lks. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-30

-----  
Found - No trace of corner stone.

14" Laurel now 16", S.73°E., 16.5 ft., no scribe, badly burnt out.

30" Fir now 34" N.29°E., 41.6 ft., opened tree for scribe "S".

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 3 W

1/4 S 13

S 24

1965

New BT - 11" D.Fir S.86°E., 9.9 ft. scribed 1/4 S24 CS BT.

Old logging road bears South about 400.0 ft.

Survey by Glenn S. Baughman, LS #536 - For: U.S. Forest Service - C.S. File 58/176-10

-----  
Found - 1965 DCSO brass cap on 1" Iron pipe firmly set, flush with the ground, properly marked.

16" Laurel, stob, with center of tree burnt out and face visible bears S.73°E., 16.5 ft. to face.

34" D.Fir, snag with scribe marks "4S" visible on an opened blaze, bears N.29°E., 41.6 ft.

11" D.Fir, high cut stump, with scribe marks "1/4 S24 CS BT" visible on an open blaze bears S.86°E., 9.9 ft.

New BTs- 6" D.Fir bears N.59°E., 29.3 ft. mkd. "1/4 S13 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

14" D.Fir bears S.89°W., 114.0 ft. mkd. "1/4 S24 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

-----  
Found - 2 1/2" brass cap (properly mkd) 1965

Original stone next to monument. continued next pg

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

|   |
|---|
| <p>17" fir with healed face with tag dated 11/07<br/>N.59°E., 29.3'<br/>Dead and down madrone with tag S.73°E., 16.0'<br/>23" Fir with healed face and tag dated 7/79 S.89°W.,<br/>114.0'<br/>32.5" Fir snag with visible scribes and tags dated<br/>7/79 &amp; 7/63 N.29°E., 41.6'</p> |
|   |