

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Pgs 7713-14)

Set a stone 14x8x5 ins., 9" in the ground, for 1/4 sec. cor. mkd. 1/4 on N. face; from which
A Fir 5" dia., bears N.25°W., 11 lks. dist. mkd. 1/4 S BT.
A Fir 11" dia., bears S.1/2°W., 58 lks. dist. mkd. 1/4 S BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd; Vern Killian - Aug. 11, 1959 - C.S. File 42/392-25

Determined by O.B.T.s:
18" Fir bears N.25°W., 7.5 ft.
14" Fir bears S.1/2°W., 38.2 ft.
At corner point found original stone and Set 3/4" x 24" Iron pipe, from which:
9" Fir bears S.59°E., 25.3 ft. mkd. 1/4 S13 BT.
8" Yew bears S.2°E., 36.0 ft. mkd. 1/4 S13 BT.
8" Cedar bears N.77°E., 35.0 ft. mkd. 1/4 S12 BT.
8" Fir bears S.54°W., 26.4 ft. mkd. 1/4 S12 BT.
Creek bears South 52.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-19

Found - I. Pipe and stone.
14" now 15" Fir S.1/2°W., 30.2 ft., shows good scar.
18" Fir N.25°W., 7.5 ft., shows good scar.
9" now 10" Fir S.59°E., 25.3 ft., shows good scar.
8" now 9" Yew S.2°E., 36.0 ft. scribe visible.
8" now 9" Cedar N.77°E., 35.0 ft. scribe visible.
8" Fir, now down, S.54°W., 26.4 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
1/4 S 12
S 13
1965

Set brass cap alongside pipe and stone.
As noted, creek South 52.0 ft. All trees in good shape.

Survey by William Ruppert - For: U.S. Forest Service - Jan. 1980 - M 79-20

Found - 2 1/2" brass cap on 1" galv. Iron pipe.
10" Yew bears S.3°E., 35.4 ft. "1/4 S13 BT" (Rec. 9", S.2°E., 36.0 ft.)
12" D.Fir bears S.61°E., 25.4 ft., good scr. (Rec. 10" Fir, S.59°E., 25.3 ft.) continued next pg

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

18" D.Fir bears N.53 3/4°W., 4.9 ft., uproot. (Rec.
18" Fir, N.25°W., 7.5 ft.)
New BT - 10" Cedar bears N.58°E., 38.5 ft. "S ¼ S12 BT".

James Klein - Keith Primm - Douglas Popham - For:
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I

Found - 2½" brass cap (properly mkd)
16.5" fir with healed face and tag dated 11/79
S.61°E., 25.4' to nail side center
12.5" yew with visible scribes and tag dated
11/19/79 S.2°30'E., 35.4'
13.7" cedar with healed face set tag dated 10/13
N.58°E., - 41.7' to nail side center.

Ron Quimby - Crew: N. Fromdahl & R. Olson - 8/2015 - C.S.
File 65/89-38

Found - DCS0 brass cap (properly mkd)
12" yew S.3°E., 35.4 down & burnt.
18" fir S.61°E., 25.4 (burnt) added spike to side center.
16" cedar N.58°E., 38.5 (burnt) added spike to side center
New - 15" hemlock S.58°W., 6.5 ft. scribed ¼ S13 BT.
6" hemlock N.46°W., 17.0 ft. scribed ¼ S 12 BT.
Note - Area badly burnt 8/2015
Creek approx. 50 south.
Hand held: Lat & Long
N 42°53'11" W 123°00'12"
Compass decl. 15½°E.