

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7716)

Set a Fir post 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S on N. face; from which
A Fir 6" dia., bears N.78 3/4°E., 44 lks. mkd. 1/4 S BT.
A Fir 12" dia., bears S.75 3/4°E., 19 lks. mkd. 1/4 S BT.

John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - July 28, 1959 - C.S. File 42/392-22

At midpoint, Set 3/4" x 30" Iron pipe, from which
30" Laurel bears N.50°W., 31.0 ft. mkd. 1/4 S1 BT.
18" Fir bears N.20°E., 23.0 ft. mkd. 1/4 S1 BT.
12" Fir bears S.87°E., 31.0 ft. mkd. 1/4 S12 BT.
NW. corner Sec. 12 bears West 2652 ft.
NE. corner Sec. 12 bears East 2652 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-16

Found - Iron pipe at 1/4 corner.
30" now 31" Laurel N.50°W., 31.0 ft.
18" now 19" Fir N.20°E., 23.0 ft., bark scribed "1/4 S1".
12" now 15" Fir S.87°E., 31.0 ft., shows good scar.
Dist. should be 26.0 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
1/4 S 1
S 12
1965

Set brass cap alongside iron pipe.
New BT - 19" Fir N.20°E., 23.0 ft. scribed 1/4 S1 CS BT.

Survey by William Ruppert, LS #856 - For: Umpqua National Forest - Jan. 1980 - M 79-20 and C.S. File 58/143(n)

Found - 2 1/2" brass cap on 1" galv. iron pipe and 3/4" galv. iron pipe.
22" D.Fir N.19 1/2°E., 22.7 ft., good scar.
24" Madrone N.50°W., 31.0 ft., good scar.
14" Fir stump S.87 3/4°E., 25.7 ft., good scar.
8" W.Fir S.25 3/4°W., 92.2 ft., good scar.

Proportioned 1/4 Corner. No monument set. True corner bears N.5°28'E., 7.05 ft. from brass cap.

continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - For: Roseburg Resources Co - Jan. 2015 - M166-29

Found - Brass cap per 1965 Douglas Co. Surveyor's Office renewal.
30" Fir N.20°E., 22.7' healed scar.
14" Fir stump S.88°E., 25.7' laying on side w/tag.
11" Fir S.3°W., 16.3' healed scar.
21" Fir S.26°W., 92.2' healed scar.
29" Madrone N.50°W., 31.0' healed scar.

James Klein - Keith Primm - Douglas Popham - For:
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I

Found - 2½" brass cap (properly mkd) 1965
33.5" D.Fir with healed face and tag dated 11/79
N.21°E., 22.7'
21" W.Fir with healed face set new tag dated
10/26/13 S.25°W., 92' to nail side center
28" madrone with remains of tag set new tag dated
10/26/13 N.49°W., 31.3'
New BT - 10" W.Fir (mkd: ¼ S12 BT) set tag dated 10/26/13
S.03°W., 16.3' to nail side center