

PRIMARY CORNER DESCRIPTION Angle point on So. bdy. Sec. 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7695)

A Sugar Pine 34" dia., on line marked with 2 notches on E. and W. sides.

Gerald V. Nygren, L.S. #1035 - For: U.S. Forest Service - March 15, 1988 - C.S. File 63/69-24

Found 46" Pine (angle point) line tree with USFS sign 52-2 attached.

New BTs- A 13" D.Fir bears N.78°W., 26.4 ft. scribed "T31S R3W S36 LINE TREE BT" with brass washer nailed to lower end of blaze.

A 7" D.Fir bears S.24°E., 14.0 ft. scribed "S1 LINE TREE BT" with brass washer nailed to lower end of blaze.

BT signs and monument signs were placed on all BTs and a 6" red band and face blazes were painted on all bearing trees.

Kris DeGroot - For: USFS - 6/2007 - C.S. File 65/60-43

Found - A 48" P.Pine with USFS Sign 54-9 nailed to the east side and a faded red paint band around the trunk.

From which bearing trees by Nygren in 1988:

A 13" D.fir sawed stump pushed 30 feet out of position by road construction bears S.60°W., 13.5 ft with scribing "BT" visible on an open face. (Rec. N.78°W., 26.4 ft)

A root hole bears S.24°E., 14.0 ft with a uprooted and rotted 7" D.fir laying alongside with scribe marks "SI LINE TREE BT" visible on an open face.

New - A 15" D.fir bears N.40°E., 30.8 ft, scribed "AP S36 BT".

A 8" D.fir bears S.44°E. 23.7 ft scribed "AP S1 BT"

All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown & distances are measured to an aluminum nail in the root crown at the side and center of the tree. All BTs have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree. Compass decl. 16¼°E.