

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 25 & 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7697)

-----  
Set a stone 16x12x12 ins., 12" in the ground, for cor. to secs. 25, 30, 31 and 36, marked with 5 notches on N. and 1 notch on S. edges; from which

A Sugar Pine 10" dia., bears N.10¼°E., 35 lks. dist. mkd. T31S R2W S30 BT.

A Fir 15" dia., bears S.29½°E., 35½ lks. dist. mkd. T31S R2W S31 BT.

A Fir 24" dia., bears S.18¼°W., 81 lks. dist. mkd. T31S R3W S36 BT.

A Fir 7" dia., bears N.39½°W., 9½ lks. dist. mkd. T31S R3W S25 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7637)

-----  
Found a granite stone 6x12x10 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general. Destroy marks on bearing trees at cor. referring to secs. 30 and 31.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: Allen Kusler - July 29, 1955 - C.S. File 42/23

-----  
Determined from O.B.Ts:

30" Fir bears S.30°E., 23.0 ft.

7" Fir snag bears N.39°W., 6.0 ft.

30" Fir bears S.18°W., 53.0 ft.

At corner point Set a 1" x 30" I. Pipe and large stone from which

16" Fir bears N.45°E., 1.0 ft. kd. S31 BT.

30" Fir bears N.35°W., 28.0 ft. mkd. S 5x BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 52/63

-----  
Found - 30" Fir N.35°W., 28.0 ft., shows scribe marks.

16" Fir, now down, N.45°E., 1.0 ft.

No trace of iron pipe.

Orig. 30" Fir, now stump, S.18°W., 53.0 ft.

Orig. 30" Fir, now down, S.30°E., 23.0 ft., shows scar.

(Cont. Next Page)

