

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 24 & 25 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7698)

-----  
Set a stone 14x10x6 ins., 10" in the ground for cor. to secs. 19, 24, 25 and 30, marked with 4 notches on N. and 2 notches on S. edges; from which

A Fir 9" dia., bears N.4 3/4°E., 25 lks. dist. mkd. T31S R2W S19 BT.

A Cedar 10" dia., bears S.60½°E., 58 lks. dist. mkd. T31S R2W S30 BT.

A Fir 35" dia., bears S.35½°W., 87 lks. dist. mkd. T31S R3W S25 BT.

A Fir 15" dia., bears N.59½°W., 35 lks. dist. mkd. T31S R3W S24 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7652 and 7653)

-----  
Found granite stone 5x8x6 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general. Destroy marks on bearing trees at cor. referring to secs. 19 and 30.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Dec. 1965 - C.S. File 52/63-32

-----  
Found - No trace of original stone.  
9" Fir stump, N.4 3/4°E., 16.5 ft., opened stump for scribed "BT".  
15" D.Fir, now 28", N.59½°W., 23.1 ft., opened tree, badly burned face, no scribing.  
35" D.Fir now 40", N.35½°W., 57.4 ft., shows good scar.

No trace of 10" Cedar because of road.

Set Brass cap at cor. mkd: County Surveyors Office 1965  
T31S S 24 | S 30 R2W  
R3W S 25

New BTs- 7" Cedar N.47°W., 5.3 ft. mkd. T31S R3W S24 CSBT.  
28" D.Fir N.59½°W., 23.1 ft. mkd. T31S R3W S24 CSBT

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I

-----  
Found - 2½" aluminum cap stamped PLS 866  
29" Fir with healed face & tag dated 4/80  
N.51°48'E., 24.0' to nail side center

continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 24 & 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>49" fir with healed face &amp; tag dated 4/80 N.54°E., 43.5' to nail side center</p> <p>17" fir with healed face &amp; tag dated 4/80 S.48°20'E., 19.5' to nail side center.</p> <p>19" fir with healed face &amp; tag dated 4/80 S.19°51'E., 18.45' to nail side center.</p>