TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7699)

Set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ on N. face; from which
A Laurel 6" dia., bears S.13 3/4°W., 8¼ lks. mkd. ¼ S BT.
A Laurel 6" dia., bears N.35°E., 10½ lks. mkd. ¼ S BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page 7622)

The ¼ sec. cor., which is a post, greatly decayed, marked and witnessed as described by the Surveyor general. I reestablish this cor. in its original position for sec. 24, T31S R3W., only, as follows:
No stones obtainable.
Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. on E. bdy. sec. 24, marked ¼ on W. face, from which
A Madrone 12" dia., bears N.66°W., 39 lks. mkd. ¼ S24 BT.
A Madrone 8" dia., bears S.13°W., 8 lks. mkd. ¼ S24 BT.

Survey by William J. Ruppert, LS #866 - For: U.S. Forest Service - April 1980 - C.S. File 58/143 (n) and M 79-43

Set 2" x 30" alum. pipe with 2½" alum. cap mkd: S24 PLS 866 1980, from which
12" Fir bears S.88°40'W., 54.6 ft. scribed "¼ S24 BT". Attached 3/4" brass washer mkd. "LS 866" to lower blaze.
13" Cedar bears S.35°W., 56.6 ft. scribed "¼ S24 BT" Attached 3/4" brass washer mkd. "LS 866" to lower blaze.

DCSO-GIS Corner visitation - 2/23/2004 - Typed: 2/10/2011 - C.S. File 67/33-1

Monument - 2" IP/BC Comment - OK

James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I & M171-2 A-D

Found - 2½" aluminum cap stamped PLS 866, 1980
29" Cedar with healed face & tag dated 10/13 S.35°W., 56.0' to nail side center
22" fir with healed face & tag dated 10/13 S.88°40"W., 55.2' to nail side center.