

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 13 & 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7700)

-----  
Set a Fir post 4 ft. long, 4" sq., 24" in the ground for cor. to secs.13, 18, 19 and 24, marked T31S S18 on NE.; R2W S19 on SE.; R3W S24 on SW.; and S13 on NW. faces, with 3 notches on N. and S. edges; from which

A Fir 10" dia., bears N.71½°E., 25 lks. dist. mkd. T31S R2W S18 BT.

A Laurel 7" dia., bears S.29°E., 28¼ lks. dist. mkd. T31S R2W S19 BT.

A Sugar Pine 48" dia., bears S.41½°W., 25 lks. dist. mkd. T31S R3W S24 BT.

A Chinquapin 8" dia., bears N.15¼°W., 41 lks. dist. mkd. T31S R3W S13 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-74

-----  
Found - 10" now 22" Fir N.71½°E., 16.5 ft., shows good scar  
7" now 10" Laurel S.29°E., 18.5 ft., opened tree, rotten.

48" now 54" Pine S.41½°W., 16.5 ft., shows good scar  
8" Chinquapin now down, N.15½°W., 27.1 ft., scribe visible "R3WS13".

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S ¼ S 13 | R2W  
R3W S 24

1966

New BTs- 8" Hemlock S.32°E., 34.4 ft. scribed T31S R2W S19 CS BT.

7" Laurel N.66°W., 27.1 ft. scribed T31S R3W S13 CS BT.

Survey by Loyd R. Moffit - For: U.S. Forest Service - Nov. 1986 - C.S. File 62/30-21

-----  
Found - 1966 DCSO brass cap on 1" I.P.  
60" Pine, dead, S.41½°W., 16.5 ft. (Rec. S.44°W. 15.7 ft.) Scar visible. Orig. BT.

8" Madrone N.66°W., 27.1 ft. (Rec. N.64°W., 27.0 ft.) Scribe visible.

26" Fir N.71½°E., 16.5 ft. (Rec. N.70°06'E., 15.9 ft.) Scar visible.

Hemlock, down, S.32°22'E., 34.7 ft.

9" Madrone S.29°E., 18.6 ft. (Rec. S.28°23'E) Rotted face. Orig. BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 13 & 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 6" Fir which bears S.84°W., 12.2 ft. scribed T31S  
R3W S24 BT, with LS washer #944 nailed to BT  
scribe.  
Record bearings/distances given are from Survey M 79-43

James Klein - Keith Primm - Douglas Popham - For:  
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I &  
M171-2 A-D

-----  
Found - 2½" brass cap (properly mkd) 1966  
31" Fir with healed face and tags dated 9/63 & 7/79  
N.71½°E., 16.5'  
10" standing dead madrone with notched face and tags  
date 9/63 & 7/79 S.29°E., 18.0'  
14.5" Fir with visible scribe set new tag S.80°W.,  
12.2'.