

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 12 & 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7701)

-----  
Set a stone 22x14x10 ins., 17" in the ground, for cor. to secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edges; from which

A Cedar 28" dia., bears N.67 3/4°E., 51 lks. dist. mkd. T31S R2W S7 BT.

A Fir 36" dia., bears S.61 3/4°E., 35 1/2 lks. dist. mkd. T31S R2W S18 BT.

A Fir 16" dia., bears S.86°W., 45 1/2 lks. dist. mkd. T31S R3W S13 BT.

A Fir 36" dia., bears N.71 1/2°W., 38 1/2 lks. dist. mkd. T31S R3W S12 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7661)

-----  
Found a basalt stone 6x12x10 ins., above ground, firmly set, mkd. and witnessed as described by the Surveyor general. Destroy marks on bearing trees at cor. referring to secs. 7 and 18.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley; R.G. Boyd - Nov. 23, 1959 - C.S. File 42/392-45

-----  
Determined by O.B.T.s:

50" Fir N.71°W., 26.0 ft.

22" Fir snag S.86°W., 30.5 ft., found scribe.

54" Fir S.62°E., 23.1 ft.

At corner point found stone and Set 3/4" x 30" Iron pipe, from which

7" Fir S.80°E., 18.0 ft. "S18 R2W BT"

10" Fir N.55°E., 25.2 ft. "S18 X BT "

5" Fir N.39°W., 11.0 ft. "S12 XX BT X"

Creek bears South 35.0 ft.

SW. Corner S. 7 (T31-2) bears North 118.0 ft.

Survey by Loyd R. Moffit, LS #944 - For: Umpqua National Forest - Aug. 1978 - M 72-76

-----  
Found 3/4" Pipe with orig. corner stone laying beside it. Set 2" Pipe with 3" brass cap stamped "T31S S12 S13 T31S R2W S18 R3W PLS 944 1978", from which

16" Fir bears N.54°E., 25.2 ft., shows scars.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 12 & 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

7" Fir bears S.80°W., 21.3 ft. scribed T31S R3W S12 BT.  
A rotten Fir snag bears S.86°W., 30.03 ft. BT scribe visible.  
A 5 ft. Fir bears N.71½°W., 25.41 ft., shows scars.

James Klein - Keith Primm - Douglas Popham - For:  
Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I &  
M171-2 A-D

-----  
Found - 3" brass cap stamped PLS 944, 1979  
23.3" Fir with healed face and tag dated 12/79  
N.58°E., 25.1'  
5" Fir snag with visible scribes N.39°15'W., 11.1'  
59" Fir with healed face and tags dated 12/79 & 1959  
N.71°W., 26.3'