

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 1 & 12 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7702-03)

-----  
Set a stone 10x10x6 ins., 7" in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on N. and 5 notches on S. edges; from which

- A Fir 12" dia., bears N.24½°E., 77 lks. dist. mkd. T31S R2W S6 BT.
- A Fir 8" dia., bears S.16½°E., 111 lks. dist. mkd. T31S R2W S7 BT.
- A Laurel 17" dia., bears S.11½°W., 38 lks. dist. mkd. T31S R3W S12 BT.
- A Fir 15" dia., bears N.32½°W., 57 lks. dist. mkd. T31S R3W S1 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #766, dted May 10, 1906 - (DCSO records Vol. 18 Page(s) 7666)

-----  
Found iron stone 4x10x6 ins., above ground, firmly set marked and witnessed as described by the Surveyor General. Destroy marks on bearing trees referring to secs. 6 and 7.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - July 28, 1959 - C.S. File 42/392-23

-----  
Determined by O.B.T.s:  
30" Fir N.24°E., 50.8 ft.  
28" Fir S.16°E., 76.0 ft.  
30" Laurel S.11°W., 25.0 ft., I rescribed S12 T31S R3W BT.  
At corner point found stone and SET Iron pipe, from which  
6" Hemlock bears S.33°W., 8.5 ft. mkd. S12 BT.  
9" Chinquapin bears N.55°W., 15.6 ft. mkd. S1 R3W BT.  
7" Chinquapin bears N.66°E., 10.4 ft. mkd. S7 R2W BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - March 25, 1970 - C.S. File 54/28-100

-----  
Found - No trace of iron pipe, falls in skid road.  
Orig. 32" D.Fir N.24°E., 50.8 ft., shows good scar.  
Orig. 29" D.Fir S.16°E., 76.0 ft., shows good scar.  
Orig. 31" Laurel N.11°W., 25.0 ft., scribe visible.  
7" Chinquapin now 10", N.66°E., 10.4 ft. scribe visible.  
6" Hemlock now 8" S.33°W., 8.5 ft. scribe visible.  
9" Chinquapin now 12", N.55°W., 15.6 ft. scribe visible.

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 1 & 12 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>Set Brass cap at cor. mkd: County Surveyors Office R T 31 S R 3 S 1 S 7 2 W S 12 S W 1970</p> <p>This cor. lies 215.2 ft. So. of closing cor. for secs. 6 &amp; 7, T31-2</p>
<p>Ron Quimby - For: Roseburg Resources Co - Dec. 2014 - M166-27 ----- Found - Brass cap per 1970 DCSO renewal 15" Hemlock S.33°W., 8.5' healed face 9' Tall -11" Chinquapin snag N.55°W., 15.6' scribe visible 12" Chinquapin N.66°E., 10.4' healed face 35" Fir N.24°E., 50.8' healed face 31" Fir S.16°E., 76.0' healed face</p>
<p>James Klein - Keith Primm - Douglas Popham - For: Williams/Pacific Connector Pipeline - 5/2015 - M166-40 A-I ----- Found - 2½" brass cap (properly mkd) 35" D.Fir with healed face set tag dated 10/13 N.24°E., 50.5' 13" chinquapin with healed face and tags dated 3/70 &amp; 12/79 N.67°E., 10.4' 26.5" madrone with tag dated 12/79 S.13°W., 25.2' 17" hemlock with healed face and tags dated 12/79 &amp; 3/70 S.34½°W., 8.5' 12" chinquapin snag with visible scribe and tags dated 1959 &amp; 12/79 N.54°W., 16.0'.</p>
<p> </p>