

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100136

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 36 only, T31-5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Ives and Hyde under Contract #39 dated Jan. 4, 1854 (DCSO records Vol. 18 Page(s) 7781)

-----  
Set ¼ sec. post on NE slope of mountain, from which  
A Vine Maple 4" dia., bears S.70°W., 10 lks.  
A Maple 12" dia., bears N.52°E., 54 lks.

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7852)

-----  
The ¼ sec. cor. is gone. I find the 1 orig. bearing trees.  
At cor. point  
Set a stone, 10x10x8 ins., 7" in the ground, for ¼ sec. cor.  
marked ¼ on W face; from which  
A Maple 12" dia., (16" now) bears N.52°E., 54 lks. dist.,  
marked ¼ S B T.  
A Vine Maple 4" dia., (7" now) bears S.70°W., 10 lks.  
dist., marked ¼ S B T.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15642)

-----  
Point for the ¼ sec. cor. of sec. 36 only, determined by the method of irregular boundaries, there is no remaining evidence of the original corner.  
Set an iron post 28" long, 2½" dia., 23" in the ground, with brass cap mkd:  
¼ S 36 |  
T 31 S |  
R 5 W |  
1973  
from which  
A Fir 9" dia., bears S.10°W., 61 lks., mkd. ¼ S36 BT.  
A Fir 7" dia., bears S.83°W., 50½ lks., marked ¼ S36 BT.

Ron Quimby - Crew: N. Fromdahl, & R. Olson - 11/2015 - C.S. File 65/95-4

-----  
Found - 3" 1973 BLM brass cap (properly mkd)  
22" Fir stump S.10°W., 40.3 ft. (scar)  
New - 7" D.Fir N.72°W., 34.0 ft. }  
4" hemlock, S.59°W., 23.1 ft. } All scribed ¼ S36 BT  
6" D.Fir N.18°W., 37.3 ft. }  
50" Maple N.4°W., 30.5 ft. }  
Note - Corner is on South boundary of old clear cut approx.  
100' south of creek.  
Dec. 15½°