

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION W. Sec. Cor. for 30 & 31 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records, Vol. 18 Page 7854)

At point of intersection, I set a stone, 14x10x6 ins., 10" in the ground, for closing cor. to secs.30 and 31, marked C C on E face, with 5 notches on N and 1 notch on S faces; from which

- A Fir 36" dia., bears N.74°E., 73 lks. dist., marked T31S R4W S30 BT.
- A Fir 20" dia., bears S.81 3/4°E., 61 lks. dist., marked T31S R4W S31 BT.
- A Fir 33" dia., bears S.39¼°W., 29 lks. dist., marked T31S R4W C C S30 and 31 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones and Joe Brady - March 1966 - C.S. File 54/20-48

Found - 36" Fir, now dead snag, N.74°E., 48.2 ft. shows scar
20" Fir now blown down, S.81 3/4°E., 40.3 ft.
33" Fir now stump, S.39¼°W., 19.1 ft. scribe visible "S3".

No trace of stone at corner.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 31 S	R
5	S 30	4
W	S 31	W
	S 25	
	S 36	
	1966	

New BT - 3" Fir N.79½°E., 19.4 ft. scribed S30 BT.

Reblazed and rescribed:

39" Fir stump S.39¼°W., 19.1 ft. scribed "T31S R5W S25 CS BT".

This corner lies in large cut unit.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15643-44)

The original closing corner, perpetuated by Powell in 1966, monumented with an iron post, 1½" dia., firmly set, protruding 8" above ground, with brass cap mkd:COUNTY SURVEYORS OFFICE

T 31 S	R 4 W
S 25	S 30
	S 31
R 5 W	
	1966

(Cont. Next Page)

