

PRIMARY CORNER DESCRIPTION W. Sec. Cor. for 19 & 30 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7859-60)

-----  
At point of intersection of line, bet. secs. 19 and 30.  
Set stone, 12x8x8 ins., 8" in the ground, for closing corner to secs. 19 and 30, marked C C on E face, with 4 notches on N and 2 notches on S faces; from which  
A Laurel 12" dia., bears N.4°E., 40 lks. dist., marked T31S R4W S19 BT.  
A Fir 7" dia., bears S.89°E., 34 lks. dist., marked T31S R4W S30 BT.  
A Laurel 16" dia., bears N.72½°W., 35½ lks. dist., marked T31S R4W CC S19 and 30 BT.

BLM resurvey by Daniel Berry and Charles Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15645)

-----  
Point for the closing cor. of secs. 19 and 30, T31S R4W; there is no remaining evidence of the original corner. No permanent monument established.

BLM resurvey by Rogers, McMullen and Bishop under Group #1217. Surveyed, Sept. 1984/April 1986 (DCSO records Vol. 47 Page(s) 18159)

-----  
Point for the closing cor. of secs. 19 and 30 at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 31 S R 4 W  
S 24  $\frac{S 19}{S 30}$  CC  
R 5 W  
1985

from which

A Fir 7" dia., bears N.10¼°E., 20 lks. dist., marked T31S R4W S19 CC BT.

A madrone 4" dia., bears S.48°E., 12 lks. dist. mkd. X BT.  
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the cor. of secs. 24 and 25, T31S R5W, bears S.0°18'E., 5.88 chs. dist.