

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100374

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 13 and 24 only, T31-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Butler Ives and Geo. Hyde under Contract #39 dated Jan. 4, 1854 (DCSO records Vol. 18 Page(s) 7779)

Set post, cor. of secs. 18, 19, 13 and 24, from which
A Fir 13" dia., bears S.26°E., 8 lks.
A Fir 24" dia., bears S.58°W., 20 lks.
A Fir 24" dia., bears N.81°W., 58 lks.
A Fir 30" dia., bears N.21°E., 23 lks.

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7863)

Intersect the W bdy. of the tp. 5.75 chs. N of cor. to Secs. 13, 18, 19 and 24, which is a post, greatly decayed, with marks obliterated, from which

A Fir 30" dia., (36" now) bears N.21°E., 23 lks. dist., marked T31S R4W S18 BT.
A Fir 13" dia., bears S.26°E., 8 lks. dist., marked T31S R4W S19 BT.
A Fir 24" dia., bears S.58°W., 20 lks. dist., marked T31S R5W S24 BT.
A Fir 24" dia., bears N.81°W., 58 lks. dist., marked T31S R5W S13 BT.

As this is a cor. to secs. 13 and 24 only, I destroy the marks on the 2 fir trees E of the cor. in T31S R4W, and remove this decayed post and set a post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 13 and 24, marked T31S S24 on SW., and R5W S24 on NW faces, with 3 notches on N and 3 notches on S edges.

Douglas Co. Surveyors Office - John Powell; Frank Jones; Joe Brady - March 1966 - C.S. File 54/20-34

Found - Orig. 24" D.Fir now snag, S.58°W., 13.2 ft., opened for scribe.

Orig. 24" D.Fir now snag, N.81°W., 38.3 ft.

Set Brass cap at cor. marked: County Surveyors Office

R	T31S	R
5	S 13	4
W	S 24	W
1966		

New BTs -6" Cedar N.20°E., 20.8 ft. scribed T31S S19 CS BT.

5" D.Fir N.36°W., 20.2 ft. scribed S13 CS BT.

BLM resurvey by D. Berry and C. Akin under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15646-47)

(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100374

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 13 and 24 only, T31-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The cor. of secs. 13 and 24 only, perpetuated by Powell in 1966, monumented with an I.P. 1½" dia., firmly set, protruding 10" above ground with properly marked brass cap. from which the remains of the original bearing trees:

A Fir 44" dia., bears N.21°E., 23 lks. dist., with healed blaze.

A Fir snag 29" dia., bears S.58°W., 20 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees marked by Powell:

A Cedar 7" dia., bears N.70°E., 31 lks. dist., with healed double blaze.

A Fir 5" dia., bears N.40°W., 29 lks. dist., with healed double blaze.

and a new bearing tree:

A Fir 6" dia., bears S.32°W., 52 lks. dist., mkd. T31S R5W S24 BT.

Fd. OK by Kris DeGroot, 3/2005 - M 146-19