

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION W. Sec. Cor. for 18 & 19 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7863)

At point of intersection, set a stone, 14x10x5 ins., 10" in the ground, for closing cor. to secs. 18 and 19, marked C C on E face, with 3 notches on N and S faces, from which
A Laurel 10" dia., bears N.65°E., 100 lks. dist., marked T31S R4W S18 BT.
A Cedar 9" dia., bears S.54°E., 62 lks. dist., marked T31S R4W S19 BT.
A Fir 30" dia., bears S.14½°W., 33 lks. dist., marked T31S R4W C C S18 and 19 BT.

Douglas Co. Surveyors Office - John Powell; Frank Jones; Joe Brady - March 1966 - C.S. File 54/20-33

Found - 14x10x5 in. stone, 3 notches on N and S edge.
Orig. 10" Laurel now 26", N.65°E., 66.0 ft., rotten but parts of scribe visible.
Orig. 9" Cedar now 34", S.54°E., 40.9 ft. shows scar.
Orig. 30" D.Fir S.14½°W., 21.8 ft. down & rotten.
Set Brass cap at cor. marked: County Surveyors Office
R T31S R
5 S 13 | S 18 4
W S 13 | S 19 W
1966
New BT - 10" D.Fir N.69°E., 23.6 ft. scribed T31S R4W S18 CS BT.

1966 County cap, 2 orig. BTs and 1 county BT Fd. OK, BLM survey by Berry and Akin, 1972-1973 (DCSO records, Vol. 38 Page 15647)

Rob Ward - 3/2001 - C.S. File 65/36-24

Found - 2½" Douglas County brass cap.
35" I.Cedar bears S.54°E., 40.9 ft., healed face.
14"x1' D.Fir stump bears N.62½°E., 23.8 ft., healed face.
New - 6" D.Fir bears S.25°W., 28.3 ft. blazed & scribed at base "X BT"
Gal. steel post set adjacent to corner. BTs have red painted band & face plus yellow BT tag.

Fd. OK by Kris DeGroot, 3/2005 - M 146-19