

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION W. Sec. Cor. for 7 & 18 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 19 Page(s) 7868)

At point of intersection
Set a stone 14x12x4 ins., 10" in the ground, for closing corner to secs. 7 and 18, marked C C on E face, with 2 notches on N and 4 notches on S faces; from which
A Fir 26" dia., bears N.29½°E., 139½ lks. dist., marked T31S R4W S7 BT.
A Fir 33" dia., bears S.33°E., 128½ lks. dist., marked T31S R4W S18 BT.
A Fir 11" dia., bears N.87½°W., 33 lks. dist., marked T31S R4W CC S7 and 18 BT.

Survey by Robert M. Thompson - For: Sunny Valley Lumber Co. - July 12, 1959 - M 15-24

Found - Unmarked stone and 3 BTs per Govt notes, in good condition, faces overgrown.
I Set aluminum tag on 7" Madrone, N.44½°E., 4.4 ft.

Douglas Co. Surveyors Office - John Powell; Frank Jones; Joe Brady - March 1966 - C.S. File 54/20-38

Found - No trace of 3 orig. BTs as called for in notes.
7" Laurel, now 7", N.44½°E., 4.4 ft. with alum. tag, not scribed.
24" D.Fir N.84°W., 21.8 ft. Opened tree for scribe, found scribe marks, could not make out.
Set Brass cap at cor. mkd: County Surveyors Office
R T 31 S R
5 S12 | S 7 4
W | S 18 W
1966
New BTs - 7" Laurel N.44½°E., 4.4 ft. scribed T31S R4W S7 CS BT.
8" Laurel S.56°E., 23.6 ft. scribed.

Brass cap, 1 orig. and 2 county BTs. found OK, by BLM resurvey, Berry and Akin under Group #800, surveyed Sept. 1972/June 1973 (DCSO records, Vol. 38 Page 15649)

Fd. OK by Kris DeGroot , 3/2005 - M 146-19