

PRIMARY CORNER DESCRIPTION E. Sec. Cor. Secs. 1 & 12 only, T31-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and Geo. Hyde, under Contract #39 dated Jan. 4, 1854 (DCSO records Vol. 18 Page(s) 7777)

Set post, cor. of secs. 6, 7, 1 and 12, from which
A Laurel 14" dia., bears N.28°E., 24 lks.
A Laurel 16" dia., bears S.67°E., 29 lks.
A Laurel 3" dia., bears S.35°W., 48 lks.
A Laurel 10" dia., bears N.11°W., 34 lks.

W.H. Byars, under contract # 456 dated July 28, 1882 (DCSO rec. Vol. 17 Pages 7159-60)

Began at cor. to secs. 1, 12, 6 and 7, which is a Fir post, 4" sq. firmly set in the ground and marked, T31S R4W S6 on the NE face, S7 on the SE face, S12 on the SW face and R5W S1 on the NW face, also one notch on the North and five notches on the South angles of the same, from which
A Laurel 14" dia., bears N.28°E., 24 lks. dist. marked T31S R4W S6 BT.
A Laurel 16" dia., bears S.67°E., 29 lks. dist., marked T31S R4W S7 BT.
Tree in Sec. 12 not recognizable.
A Laurel 10" dia., bears N.11°W., 34 lks. dist., marked T31S R5W S1 BT.

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 19 Page(s) 7871-72)

Intersect the W bdy. of the tp. and set temp. post. The post cor. set for secs. 1, 6, 7 and 12 is gone. I find 2 witness trees.
At cor. point
A set a stone, 16x8x6 ins. 12 ins. in the ground, for cor. to secs. 1 and 12, marked with 1 notch on N and 5 notches on S edges; from which
A Laurel 14" dia., bears N.28°E., 24 lks. dist. marked T31S R4W S6 BT.
A Laurel 16" dia., bears S.67°E., 29 lks. dist., marked T31S R4W S7 BT.
The bearing trees in secs. 1 and 12 are destroyed by fire. I mark 2 new trees as follows:
A Fir 32" dia., bears S.13°W., 109½ lks. dist., marked T31S R5W S12 BT.
A Laurel 12" dia., bears N.13°W., 35 3/4 lks. dist., marked T31S R5W S1 BT.
As this is a cor. to secs. 1 and 12, I destroy the marks on the 2 Laurels E of this cor. in T31S R4W.

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100569

PRIMARY CORNER DESCRIPTION E. Sec. Cor. for 1 and 12 only, T31-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John Powell; Frank Jones; Joe Brady - April/May 1966 - C.S. File 54/20-52

Found - 32" Fir now 36", S.13°W., 72.2 ft. opened tree for scribe.

No trace of NW BT.

Set Brass cap at cor. mkd: County Surveyors Office

R R
5 S 1 | S 7
W S 12 | W 4
1966

New BTs -8" D.Fir S.17½°W., 9.0 ft. scribed T31S R5W S12 CS BT.

12" D.Fir N.50°W., 11.0 ft. scribed T31S R5W S1 CS BT.

Brass cap and 3 BTs, Fd. OK. by BLM resurvey by Berry and Akin, under Group #800, Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15650-51)