

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION W. Sec. Cor. for 6 & 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. M. Bushey, under Contract #620 dated June 17, 1893 (DCSO records Vol. 19 Page(s) 7873)

At point of intersection, set a stone, 12x8x8 ins. 8 ins. in the ground, for closing cor. to secs. 6 and 7, marked C C on E face; with 1 notch on N and 5 notches on S faces, from which

A Fir 24" dia., bears N.86°E., 255 lks. dist., marked T31S R4 W S6 BT.

A Laurel 14" dia., bears S.13 3/4°E., 119 lks. dist., marked T31S R4W S7 BT.

A Laurel 6" dia., bears S.36½°W., 64 lks. dist., marked T31S R4W C C S6 and 7 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. Aug. 18, 1959 (Witnesses: R.G. Boyd, A. Keatley & J.L. Markham - C.S. File 42/391-33)

Corner as determined by O.B.T.

34" Fir bears N.86°E., 168.3 ft.

At corner point, found stone and set 1" x 50" Drill steel, from which

5" Laurel bears S.15°W., 5.8 ft. mkd. S7 T31S R4W BT.

4" Laurel bears N.22°E., 12.2 ft. mkd. S6 T31S BT.

4" Fir bears N.1°E., 16.9 ft. mkd. S6 BT.

4" Laurel bears N.44°W., 8.8 ft. mkd. S1 T31S R5W BT.

Douglas Co. Surveyors Office - John Powell; Frank Jones; Joe Brady - April/May 1966 - C.S. File 54/20-51

Found - 1" steel drill at corner.

Orig. 34" Fir now 37", N.86°E., 168.3 ft. shows good scar.

5" now 7" Laurel S.15°W., 5.8 ft. bark scribed "BT".

4" now 6" Laurel N.44°W., 8.8 ft. bark scribed "S1 T31S R5W".

4" now 6" Laurel N.22°E., 12.5 ft. bark scribed.

4" now 6" D.Fir N.1°E., 16.9 ft. shows good scar.

Reblazed and rescribed:

7" Laurel S.15°W., 5.8 ft. scribed "T31S R5W S1 CS BT."

6" Laurel N.44°W., 8.8 ft. scribed T31S R5W S1 CS BT."

Cor. Fd. OK, 1966 I.R., 1 orig. and 4 county trees - by BLM survey, Berry and Akin, under Group #800, Surveyed, Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15651)

