

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 100629

PRIMARY CORNER DESCRIPTION East 1/4 Cor. for Sec. 1 only, T31-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Butler Ives and Geo. Hyde, under Contract #39, dated Jan. 4, 1854 (DCSO records Vol. 14 Page(s) 7777)

-----  
Set ¼ sec. post, on E slope of mountain, from which  
A Fir 5" dia., bears S.10°E., 34 lks.  
A Redwood 12" dia., bears S.22°W., 89 lks.

BLM resurvey by Daniel Berry and Charles Akin, under Group #800. Surveyed Sept. 1972/June 1973 (DCSO records Vol. 38 Page(s) 15651-52)

-----  
Point for the ¼ sec. cor. of sec. 1 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

¼ S 1  
T 31 S  
R 5 W  
1973

from which

A Fir 8" dia., bears S.71°W., 44 lks. dist., mkd. ¼ S1 BT.  
A Fir 23" dia., bears N.23°W., 43½ lks. dist., mkd. ¼ S1 BT.