

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 and 5 & 6, T32-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7782)

Set Post, cor. to secs. 5, 6, 31 and 32, from which
A Fir 14" dia., bears N.52°E., 29 lks. dist.
A Laurel 8" dia., bears S.40°E., 12 lks. dist.
A Laurel 5" dia., bears S.20°W., 26 lks. dist.
A Laurel 6" dia., bears N.78°W., 9 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7848-49)

The Sec. cor., which is a post, partly burnt, with marks obliterated, I find the 4 original witness trees standing but have been killed by fire.
I remove this post, and set a stone, 14x12x4 ins., 10" in the ground, for cor. to secs. 5, 6, 31 and 32, marked with 5 notches on E. and 1 notch on W. edges; from which
A Fir 14" dia., bears N.52°E., 29 lks. dist., mkd. T31S R4W S32 BT.
A Laurel 8" dia., bears S.40°E., 12 lks. dist., mkd. T32S R4W S5 BT.
A Laurel 5" dia., bears S.20°W., 26 lks. dist., mkd. T32S R4W S6 BT.
A Laurel 6" dia., bears N.78°W., 9 lks. dist., mkd. T31S R4W S31 BT.
I mark 4 new witness trees as follows:
A Fir 32" dia., bears N.39°E., 35½ lks. dist., mkd. T31S R4W S32 BT.
A Laurel 5" dia., bears S.35 3/4°E., 20 lks. dist., mkd. T32S R4W S5 BT.
A Laurel 12" dia., bears S.57 3/4°W., 90 lks. dist., mkd. T32S R4W S6 BT.
A Fir 12" dia., bears N.1½°W., 271 lks. dist., mkd. T31S R4W S31 BT.

Survey by George J. Wenderoth, Deputy Co. Surveyor - Wit: Clifford Worley - 1950 - C.S. 40/246

Find old BT and stake.
Drive 1" Pipe for corner.
Scribe - 6" Chinquapin N.44°26'W., 9.0 ft.
7" Chinquapin N.45°00'E., 42.6 ft.
7" Madrone S.47°00'E., 22.2 ft.
7" Madrone S.45°55'W., 26.5 ft.

cont.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO remonumentation by Hans W. Thielsen, under Group # 350, Surveyed, May/June 1959 - (DCSO rec. Vol. 30 Pages 12789-90)

The Sec. cor., remonumented with an iron pipe, 3/4" dia., set by the County Surveyor in 1950, from which the remaining original bearing tree:

A sawed Fir stump 36" dia., bears N.52°E., 29 lks., mkd. BT on opened blaze.

and bearing trees mkd. in 1950:

A Chinquapin 8" dia., bears N.45°E., 65 lks., mkd. T31S R4W S32 CS BT.

A Madrona 6" dia., bears S.51°E., 35 lks., mkd. T32S R4W S5 CS BT.

A Madrona 6" dia., bears S.33°W., 41 lks., mkd. T32S R4W S6 CS BT.

A Madrona 8" dia., bears N.35°W., 14 lks., mkd. T31S R4W S31 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T31S R4W
S 31 S 32
S 6 S 5
T32S
1959

Reset iron pipe alongside iron post.

Fd. OK, July 1994 by R. Templin - Partition 1995-0115 A&B

FD. Ok by Shaner, 12/1996 - C.S. File 65/13-1L & RM4-3

Rob Ward, Ward NW INC. - For: Seneca Jones Timber Co. - 2/2004 - M 144-9

Condition report only

Found - 3" BLM brass cap dated 1959

36" rotted Fir stump bears N.52°E., 19.1', no visible marks.

10" Chinquapin snag bears N.45°E. 42.9' -healed face

9" Madrone bears S.51°E., 23.1' - healed face.

8" Madrone bears S.33°W., 27.1' - visible scribing.

13" Chinquapin (rec. Madrone) bears N.35°W., 9.2' healed face.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 and 5 & 6, T32-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2627; Surveyed April/May 2013 - (DCSO records Vol. 58 Page(s) 23062-3)

The cor. of secs. 5, 6, 31, & 32, on the N. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground, w/brass cap (properly) mkd. from which the remains of an original bearing tree

A sawed and rotted fir stump, 35" dia., bears N.52°E., 19.1 ft., no marks visible.

and the remains of BTs mkd. by Wenderoth, in 1946

A chinquapin snag, 11" dia., bears N.44¼°E., 42.2 ft., with a healed blaze. (Record, N.45°E., 42.9 ft.)

A madrone, 10" dia., bears S.52¼°E., 22.5 ft., with a healed double blaze. (Record, S.51°E., 23.1 ft.)

A madrone, 8" dia., bears S.32°W., 26.7 ft., with a healed blaze. (Record, S.33°W., 27.1 ft.)

A chinquapin, 13" dia., bears N.35°W., 9.2 ft., with a healed double blaze. (Record, madrone)

and a new bearing tree

A fir, 12" dia., bears N.27¾°E., 35.0 ft., mkd. T31S R4W S32 BT.

An iron pipe, ¾" dia., is alongside the iron post.

Daniel Baker - For: Weyerhaeuser - 7/2019 - M176-18A-C

Found - ¾" BLM BRASS cap "1959" 13" fir, N.27°E., 34.8' (REC.= N.27¾°e., 35.0') to nail side/center-2013 BLM BT.

11" madrone, S.53°E., 22.4' (rec.= S.52¼°E., 22.5') to nail side/center- CS 40/246 BT.

9" madrone, S.33°W., 26.6' (rec. = S.32°W., 26.7') to nail side/center- CS 40/246 BT

14" Chinquapin, N.35°W., 9.1' (rec. = N.35°W., 9.2') to nail side/center-CS40/246 BT