TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7855-56)

Set a stone 18x8x6 ins., 12" in the ground for ¼ sec. cor. marked ¼ on W. face; from which
A Fir 30" dia., bears N.66½°W., 40 lks. dist. mkd. ¼ S BT.
A Fir 24" dia., bears N.15°E., 36 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham - Oct. 7, 1959 - C.S. File 42/391-38

Determined by O.B.T.s:
38" Fir N.66½°W., 28.0 ft.
36" Fir N.15°E.,23.7 ft.
At corner point found stone and SET 2½" x 36" Iron pipe, from which
7" Fir bears N.17°E., 88.0 ft. mkd. ¼ S29 BT.
8" Alder bears S.20°E., 141.0 ft. mkd. ¼ S29 T31S R4W BT.
Road bears East, 45.0 ft.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18156)

The ¼ sec.cor., perpetuated and recorded by Markham in 1959, monumented with the original stone, 14x7x5 ins., loosely set, projecting 12" above ground, mkd. ¼ on W. face, (alongside of which is an iron pipe, 2¼" dia., firmly set, projecting 12' above ground) from which the original bearing trees:
A Fir 47" dia., bears N.15°E., 36 lks. dist., with healed blaze.
A Fir 40" dia., bears N.66½°W., 40 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S R 4 W
¼
S 30 | S 29
1984

Deposit original stone and iron pipe alongside the iron post.