

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7856)

Set a stone 18x10x6 ins., 12" in the ground for cor. to secs. 19, 20, 29 and 30, marked with 5 notches on E. and 2 notches on S. edges; from which

A Fir 36" dia., bears N.14¼°E., 425 lks. dist. mkd. T31S R4W S20 BT.

A Fir 48" dia., bears S.3½°E., 75 lks. dist. mkd. T31S R4W S29 BT.

A Fir 12" dia., bears S.31¼°W., 78½ lks. dist. mkd. T31S R4W S30 BT.

A Fir 12" dia., bears N.83°W., 140 lks. dist. mkd. T31S R4W S19 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham; R.G. Boyd - Oct. 7, 1959 - C.S. File 42/391-36

Determined by O.B.T.s:

40" Fir S.3½°E., 49.5 ft.

24" Fir N.83°W., 92.4 ft.

At corner point, found stone and SET 1" x 48" Iron pipe, from which

9" Fir S.5°W., 7.9 ft. mkd. S29 BT.

9" Fir N.85°E., 8.4 ft. mkd. S20 T31S BT.

6" Fir N.28°W., 2.7 ft. mkd. S19 BT.

7" Fir S.85°W., 5.7 ft. mkd. S30 BT.

Road bears South 265.0 ft.

Road bears East, 265.0 ft.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18157)

The sec. cor., perpetuated and recorded by Markham in 1959, monumented with the original stone, 18x10x6 ins., firmly set, projecting 10" above ground, with 2 notches on S. edge, (alongside of which is an iron pipe, 1" dia., firmly set, projecting 10" above ground,) from which the remains of the original bearing trees:

A decayed Fir stump 40" dia., bears N.14¼°E., 425 lks. dist., no marks visible.

A Fir 45" dia., bears S.3½°E., 72 lks. dist., with healed blaze. (Rec. 75 lks.)

and bearing trees mkd. by Markham:

A Fir 13" dia., bears N.80°E., 13 lks. dist., with healed double blaze. (Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 15" dia., bears S.3°W., 11 lks. dist., with healed double blaze.

A Fir 11" dia., bears S.86°W., 8 lks. dist., with healed double blaze.

A Fir 6" dia., bears N.22°W., 3 lks. dist. with fragmentary scribe marks visible on partially healed double blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T	31	S	R	4	W
	S	19		S	20
	S	30		S	29
				1985	

from which a new bearing tree:

A Fir 20" dia., bears N.31°W., 28 lks. dist., mkd. T31S R4W S19 BT.

Deposit original stone and iron pipe alongside, and white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. Ok by Tony Hostetter, 11/2007 - M154-51