

PRIMARY CORNER DESCRIPTION W C 1/4 Cor. for Secs. 5 and 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 19 Page(s) 7874)

Set a stone 14x8x4 ins., 10" in the ground, for 1/4 sec. cor. marked 1/4 on W. face; from which

A Yew 14" dia., bears S.16 1/4°W., 38 1/2 lks. mkd. 1/4 S BT.

A Fir 6" dia., bears N.41°E., 42 1/2 lks. dist. mkd. 1/4 S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - June 11, 1956 - C.S. File 47/89

Found stake set in location of original Yew tree. Tree was knocked over during road construction. Stake was set by Richard Hamlin to preserve location.

Corner fell on cut bank so SET WITNESS CORNER 25.0 ft. South. Set iron pipe with brass cap mkd: County Surveyors Office

T 31 S R 4 W

Wit Cor. 1/4 S6*S5

true cor. 25' North

1956

from which

A 16" W.Fir bears S.43°W., 6.3 ft. mkd. 1/4 S6 CS BT.

A 14" W.Fir bears S.22°E., 23.5 ft. mkd. 1/4 S5 CS BT.

Fd. Witness corner OK, April 1996 by Ken Hoffine - M 123-69

Ken Hoffine, Lone Rock Timber Co. - 2/14/2013 - C.S. 65/78-8

Found - 1956 County Cap (properly mkd) 1.0 Ft. above ground on the upper cut of existing rock road grade.

33" D.Fir bears S.35 3/4°W., 6.5 Ft. (Record from M123-69 S37°W 6.2 Ft.) healed face and tag

19" D.Fir stump bears S.24°E., 23.1 ft. (record from M123-69 S.24 1/2°E., 22.9 Ft.) partial face.

New - 13" D.Fir bears N.26 1/2°E., 47.6 ft. We Scribe BT and nail aluminum BT tag to the tree

The south end of a rail car bridge bears N.5°W., 112 ft

Note: Lone Rock Timber ran a random traverse along the sec. lines from the east 1/4 corner to the SE sec. corner to the south 1/4 corner to the SW sec. corner of sec. 6. To mark property lines for timber management purposes. We also ran a GPS survey for survey control at points on our boundary tags. Fd witness corner above east cut bank of 31-5-12 rd, and approx. 112 ft. from the south end of a rail car conventional traverse to check our closure. We marked the property lines with flagging, blazing, painting and aluminum bridge that crosses a tributary of O'shea creek.

Cont.

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION W C 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Lone Rock Timber Co. - Nov. 2013 - M 166-6
& C.S. File 65/81-1

Condition report only

Found - 1956 county cap for witness corner which is South 25
ft from true position.

33" D.Fir bears S.35 $\frac{3}{4}$ °W., 6.5 ft (record S.37°W.,
6.2 ft) healed face and tag.

19" D.Fir stump bears S.24°E., 23.1 ft (record
S.24 $\frac{1}{2}$ °E., 22.9 ft) partial face

13" D.Fir bears N.26 $\frac{1}{2}$ °E., 47.6 feet (as per record)
visible scribing and tag.

Witness corner lies on East cut bank of 31-5-12.0 RD, true
corner position would fall in roadway. Corner is also approx.
112 feet from the south end of a railcar bridge that crosses
a tributary of O'Shea Creek.