

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol 18 Pages 7861-62)

Set a stone 14x11x5 ins., 10" in the ground for ¼ sec. cor. marked ¼ on N. face; from which

A Fir 6" dia., bears N.68¼°E., 36 lks. dist. mkd. ¼ S BT.

A Fir 4" dia., bears S.11°W., 17½ lks. dist. mkd. ¼ S BT.

U.S. Bureau of Land Management, Roseburg District - Surveyed by Alex Tupyi - survey date: Oct. 1977 **(approved as administrative survey July 19, 1979)** - M 81-17

Set 7/8" I.P., 24" long, 18" in ground, from which

A Madrone 6" dia., bears N.87°W., 10.4 ft.

A D.Fir snag 36" dia., bears N.18°W., 15.4 ft.

Douglas Co. Surveyors Office - Stephen J. Flause, Deputy - Karen Mosely, crew - June 9, 1981 - C.S. File 61/24-32

Found - 7/8" Iron pipe leaning slightly SW., firmly set and protruding 8" above ground.

6" Madrone now 9", bears N.87°W., 8.3 ft. (Rec. N.87°W., 10.4 ft. was apparently a measurement to the tree trunk and not to the root crown) Tree is unscribed and is tagged with a BLM BT tag.

36" D.Fir snag, now a 34" (DBH) approx. 45 ft. tall snag bears N.22½°W., 16.7 ft. (Rec. N.18°W., 15.4 ft. apparently a face measurement) Tree is not scribed and has a BLM tag.

This ¼ cor. from a U.S. BLM administrative survey filed in DCSO records as M 81-17.

New BT - 10" Madrone bears S.38°E., 38.3 ft. and bark scribed "¼ S20 CS BT".

Rob Ward - For: Seneca Jones Timber Co. - 7/2011 - C.S. File 65/74-11

Found - 7/8" iron pipe, set by BLM per M81-17, with the following accessories;

12" Madrone bears N.87°W. 8.3' w/BLM BT tag no marks
21" D.Fir rotted staub bears N.22½°W., 16.7' WITH BLM tag. No marks

14" Madrone bears S.38°E. 38.3' (healed bark scribe)

New BT - 9" D.Fir bears N.9°W., 21.9' blazed, scribed "¼ S17 BT"