

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7783)

Set post, cor. to secs. 4, 5, 32 and 33, from which
A W.Oak 8" dia., bears N.42°E., 27 lks. dist.
A Fir 36" dia., bears S.50°E., 62 lks. dist.
A B.Oak 24" dia., bears S.75°W., 49 lks. dist.
A Laurel 18" dia., bears N.30°W., 75 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7846-47)

The Cor. to secs. 4, 5, 32 and 33, which is a post, greatly decayed, with marks obliterated. I find 3 of the original witness trees.

I remove this post, and set a stone, 16x12x8 ins., 12" in the ground for the sec. cor. and marked with 4 notches on E. and 2 notches on W. edges; from which

An Oak 8" dia., (10" now) bears N.42°E., 27 lks. dist., marked T31S R4W S33 BT.

An Oak 24" dia., bears S.75°W., 49 lks. dist., marked T32S R4W S5 BT.

A Laurel 18" dia., bears N.30°W., 75 lks. dist., marked T31S R4W S32 BT.

The Fir witness tree in sec. 4 is burned. In its stead I mark:

A Fir 40" dia., which bears S.51¼°E., 128 lks. dist., T32S R4W S4 BT.

Survey by George Wenderoth, Deputy Co. Surveyor - Wit: F. Loso - April 1950 - C.S. File 40/246

Found - 48" Fir S.51°15'E., 84.5 ft.

30" B.Oak S.75°W., 32.3 ft.

Drive 1" I.Pipe for corner.

Scribe - 14" Fir N.45°15'W., 33.1 ft.

10" Maple N.39°25'E., 50.3 ft.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12789)

The Sec. cor., perpetuated with an iron pipe, 3/4" dia., set by the County in 1950, from which bearing trees mkd. in 1950:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Maple 10" dia., bears N.39¼°E., 76 lks. dist., marked T31S R4W S33 CS BT.

A Fir 14" dia., bears N.45¼°W., 50 lks. dist., marked T31S R4W S32 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T 31S R4W	
<u>S 32</u>	<u>S 33</u>
S 5	S 4
1959	

from which new bearing trees

A Fir 8" dia., bears S.72°E., 25 lks. dist., marked T32S R4W S4 BT.

A Fir 10" dia., bears S.22°W., 26 lks. dist., marked T32S R4W S5 BT.

A Fir 10" dia., bears N.70°W., 28 lks. dist., marked T31S R4W S32 BT.

Reset iron pipe alongside iron post.

Cor. Fd. and used in BLM resurvey by Roseberry & Evans, Group #778, surveyed July/Sept. 1972 (DCSO records, Vol. 38 15469)

FD. Ok by B. Shaner, 12/96 - C.S. File 65/13-1 L, & R..M. 4-3

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2627; Surveyed April/May 2013 - (DCSO records Vol. 58 Page(s) 23060-1)

 The cor. of secs. 4, 5, 32, & 33, on the N. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A rotted black oak stump, size indeterminate, bears S.69½°W., 32.3 ft., with reverse scribe marks BT visible on detached face.

A madrone, 20" dia., bears N.33¾°W., 48.4 ft., with a healed lower blaze and illegible scribe marks visible on rotted upper blaze. (Record, N.34¼°W., 49.5 ft.)

and the remains of a bearing tree mkd. by Bushey in 1894

A sawed and rotted fir stump, 44" dia., bears S.49°E., 84.5 ft., no marks visible.

and BTs mkd. by Wenderoth, in 1950

A double maple, 19" dia., bears N.36¼°E., 50.2 ft., no marks visible on rotted face.

A fir, 23" dia., bears N.48¾°W., 33.0 ft., with a healed blaze.

continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T32-4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

and the remains of BTs mkd. by Thielsen in 1959
A sawed fir stump, 19" dia., bears S.75½°E., 13.8 ft., no marks visible. (Record, 14.5 ft.)
A fir, 17" dia., bears S.17¾°W., 16.3 ft., with a healed blaze. (Record, S.20°W., 17.2 ft.)
A fir, 18" dia., bears N.70°W., 17.1 ft., with a healed blaze. (Record, 18.5 ft.)
and a new bearing tree
A fir, 13" dia., bears S.48°E., 35.5 ft., mkd. T32S R4W S4 BT.
New BT has a 2½"x¼" magnetic nail (Mag Nail) driven at the base on right side center.
NAD 1983 (2011)
Latitude: 42°48'43.12" N. Longitude: 123°11'56.65" W.