

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7789)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.30°E., 21 lks. dist.
A Fir 10" dia., bears S.40°W., 8 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7846)

The ¼ sec. cor. is burned. I find 1 bearing tree at cor. point. Set a stone 14x14x14 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face; from which
A dead Fir 12" dia., bears N.30°E., 21 lks. dist. mkd. ¼ S BT.
The other witness tree is burned.
I mark 2 new witness trees as follows:
A Laurel 5" dia., bears S.64½°E., 36½ lks. dist. mkd. ¼ S BT.
A Fir 16" dia., bears N.58½°W., 126 lks. dist. mkd. ¼ S BT

George J. Wenderoth - 1949 - C.S. File 40/250 B

Set 1" I.Pipe at corner, from which
16" Fir S.14°30'E., 4.3 ft.
16" Fir S.85°30'W., 21.2 ft.

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15482)

The ¼ sec. cor. of secs. 32 and 33, perpetuated and recorded by Wenderoth in 1949, monumented with an iron pipe, 1" dia., firmly set, protruding 6" above ground, from which the remains of the bearing trees mkd. by Bushey:
A sawed Fir stump 24" dia., bears N.62°W., 126 lks. dist., with scribe mark S visible on open blaze. (Rec. N.58½°W.)
and a bearing tree mkd. by Wenderoth:
A Fir 16" dia., bears S.17¼°E., 7 lks. dist. with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:
T 31 S R 4 W
¼
S 32|S 33
1972 (Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a new bearing tree:
A Fir 12" dia., bears N.87 3/4°W., 36 lks. dist., mkd. ¼
S32 BT.
Reset iron pipe alongside iron post.

FD. Ok by B. Shaner, 12/96 - C.S. File 65/13-1 I, & R.M. 4-3

Found OK by R. Rice, Feb. 2004 - M144-9