

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7790)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears N.28°W., 10 lks. dist.  
A Fir 8" dia., bears S.75°E., 49 lks. dist.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7845)

-----  
The ¼ sec. cor. which is a post, greatly decayed, marked ¼ S on W. face. I find the 2 original witness trees. I remove this post and set a Fir post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which  
A Fir 30" dia., bears N.28°W., 10 lks. dist. mkd. ¼ S BT  
A Fir 8" dia., bears S.75°E., 49 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - G.J. Wenderoth, Deputy - Wit:  
F. Loso - March 1949 - C.S. File 40/245

-----  
Found - 40" Fir BT, N.28°W., 6.6 ft.  
16" Fir BT, S.75°E., 32.3 ft.  
Drove 1½" Iron pipe for corner.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 54/20-13

-----  
Found - I.Pipe and scribed stake at cor. scribed "CS".  
40" Fir now 48", N.28°W., 6.6 ft., shows good scar.  
16" Fir now 23", S.75°E., 32.3 ft., tree has been opened.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 4 W  
¼ S29|S28  
1966

Reblazed and rescribed:  
23" Fir S.75°E., 32.3 ft. scribed ¼ S28 CS BT.

Fd. and Used in BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15486)

Fd. BC & BTs per rec. 2/2016 - By C. Sweeden