

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7837)

Set a stone 16x14x10 ins., 12" in the ground, for 1/4 sec. cor. mkd. 1/4 on W. face, from which
A Fir 36" dia., bears N.62 3/4°E., 85 lks. dist. mkd. 1/4 S BT.
A Fir 36" dia., bears N.78 3/4°W., 143 lks. dist. mkd. 1/4 S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: J.R. Markham; R.G. Boyd - Oct. 7, 1959 - C.S. File 42/391-40

Determined by O.B.T:
40" Fir bears N.63°E., 56.1 ft., found scribe.
At corner point, SET stake, from which
4" Chinquapin bears N.27°E., 13.2 ft. mkd. 1/4 S21 BT.
5" Fir bears N.40°W., 16.4 ft. mkd. 1/4 S20 BT.
5" Fir bears S.82°W., 8.2 ft. mkd. 1/4 S20 BT.
Top of ridge bears North, 75.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - April 1966 - C.S. File 54/20-43

Found - Orig. 40" D.Fir now 40", N.63°E., 56.1 ft. Tree had been opened, faint scribe visible.
4" now 6" Chinquapin N.27°E., 13.2 ft., scribed "1/4 S21 BT"
5" now 8" D.Fir N.40°W., 15.4 ft., shows good scar.
5" now 7" D.Fir S.82°W., 8.2 ft., some scribe marks visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 4 W
1/4 S 20 | S 21
1966

All bearing trees in good condition.
Corner lies 75.0 ft. South of ridge top.

Ron Rice - For Seneca Jones Timber Co. - 6/2008 - M156-22

Found - 2 1/2" DC BC dated 1966
43" D.Fir bears N.63°E., 56.1', healed face.
19" D.Fir bears N.40°W., 15.4', healed face.
19" D.Fir bears S.82°W., 8.2', healed face.
9" Chinquapin bears N.27°E., 13.2', rotted face.