

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7839)

Set a stone 14x10x8 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which

A Fir 10" dia., bears N.33½°W., 31 lks. dist. mkd. ¼ S BT

A Laurel 12" dia., bears S.31 3/4°E., 17½ lks. dist. mkd. ¼ S BT.

Douglas County Surveyors Office - James W. Byron, Surveyor
John M. Powell and crew - C.S. File 54/20-7 - 1966

Corner searched for, not found.

Tony Hostetter - For: Roseburg Resources - Jan. 2011 - M162-3

Found - No evidence of original corner or accessories.

Set - 5/8"x36" rebar with aluminum cap marked "T31S, R4W, S17 S16, ¼, LS 1975, 2011", from which:

15" madrone, scribed "S16 ¼ BT", bears N.15°E., 5.7 ft to spike.

26" D.Fir, scribed "S16 ¼ BT" bears S.54°E., 17.2 ft to spike.

12" fir, scribed "S17 ¼ BT" bears S.70°W., 8.3 ft to spike.

14" fir, scribed "S17 ¼ BT", bears N.83°W., 8.9 ft to spike.