

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7841)

A Fir tree, 16" dia., which I mark $\frac{1}{4}$ S on W. face, for $\frac{1}{4}$ sec. cor., from which

A Fir 28" dia., bears N.53 $\frac{1}{2}$ °W., 15 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Fir 26" dia., bears S.42 3/4°E., 23 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: George Vaughn - June 6, 1951 - C.S. File 40/232

Determined by O.B.Ts

A Fir 36" dia., bears S.43°E., 17.0 ft.

A Fir 30" dia., bears N.53 $\frac{1}{2}$ °W., 10.0 ft.

At corner point found 24" Fir marked on West face.

I Remarked all original BTs.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones &
Joe Brady, crew - March 1966 - C.S. File 54/20-5

Found - 24" Fir corner tree, scribe visible, " $\frac{1}{4}$ S" on W. face.

Orig. 30" now 36" D.Fir S.43°E., 17.0 ft., shows good scar.

Orig. 30" D.Fir stump N.53 $\frac{1}{2}$ °W., 10.0 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 4 W

$\frac{1}{4}$ S8|S9

1966

New BT - 10" D.Fir N.12°E., 4.3 ft. scribed $\frac{1}{4}$ S CS BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18148)

The $\frac{1}{4}$ sec. cor., perpetuated and recorded by Markham in 1951, monumented with the original corner tree, a Douglas Fir, 28" dia., with healed blaze on W. side, from which the remains of the original bearing trees:

A Fir 38" dia., bears S.42 3/4°E., 23 lks. dist., with healed blaze.

A Fir stump, 34" dia., bears N.53 $\frac{1}{2}$ °W., 15 lks. dist., with healed blaze.

and bearing trees of no known record:

A Fir 18" dia., S.71°W., 20 lks. dist., healed blaze.
(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 16" dia., bears N.10°W., 6 lks. dist., with healed blaze.
and a reference point set by the County in 1966:
An Iron post, 1" dia., firmly set, projecting 14" above ground, bears West, 3 lks. dist., with brass cap mkd.
COUNTY SURVEYORS OFFICE T31S R4W ¼ S8 S9 1966.

Fd. Ok by Mark Smalley, Aug. 2003 - C.S. 65/48-4