

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7842)

 Set a Dogwood post, 4 ft. long, 4" sq., 24" in the ground, for cor. to secs. 4, 5, 8 and 9, marked T31S S 4 on NE.; R4W S9 on SE.; S8 on SW.; and S5 on NW. faces, with 4 notches on E. and 5 notches on S. edges, from which

- A Dogwood 6" dia., bears N.23°E., 17½ lks. dist. mkd. T31S R4W S4 BT.
- A Yew 11" dia., bears S.61°E., 69½ lks. dist. mkd. T31S R4W S9 BT.
- A Fir 12" dia., bears S.77½°W., 36 lks. dist. mkd. T31S R4W S8 BT.
- A Fir 28" dia., bears N.26°W., 18½ lks. dist. mkd. T31S R4W S5 BT.

Douglas Co. Surveyors Office - M Lenora Ladig - Karen Cheney - Pete Earle - 6/16/1976 - C.S. file 59/15-18

 Found an unrecorded 5/8" I.P. at end of cutting line. In old cat rd. Also a BLM line tag (posted 1966 by Miller & Olson) on 30" forked Yew S.87°E., 17.5 ft. from I.P.
 Made a thorough search of Hill side but fd no evidence of BTs or line trees.
 The I.P lies in area good for Orig. 1894 line calls.
 Note - Did **NOT** monument this corner.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18149)

 Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 4 W	S 5	S 4
	S 8	S 9
	1985	

- from which
- A Fir 8" dia., bears N.33°E., 35 lks. dist. mkd. T31S R4W S4 BT.
 - A Fir 8" dia., bears S.64°E., 29 lks. dist. mkd. T31S R4W S9 BT.
 - A Fir 12" dia., bears S.77¼°W., 30½ lks. dist. mkd. T31S R4W S8 BT.
 - A Fir 29" dia., bears N.82¼°W., 76½ lks. dist. mkd. T31S R4W S5 BT.
- continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Greg Lang - 12/31/2013 - C.S. File 65/82-7

Found - Brass cap set by BLM in 1985.
20" Fir stump bears S.76¼°W., 19.60' (record S.77¼°W., 20.13')
32" D.Fir bears N.83°W. 51.30' (rec N.82¼°W. 50.49')
15" D.Fir bears S.64°E., 18.30' (rec S.64°E. 19.14')
20" D.Fir bears N.32°E., 21.80' (rec N.33°E. 23.10')
3/4" iron pipe bears N.14°E., 7.84'
New - 25" D.Fir bears S.5½°W., 55.80' scribed "T31S R4W S8 BT"
Note - Bearing is to the center of the tree and distance is measured to a spike in the side of the tree.
Corner lies at the bottom of a steep west slope.