



TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

From this point United States Geological Survey triangulation station "HYDE, 1953" bears N.47°23'30"W., 119.08 chs. dist., monumented with a standard brass tablet, 3½" dia., firmly set in boulder, flush with ground, with top mkd. US GEOLOGICAL SURVEY HYDE 1953 and a triangle.

Jerry Estabrook - For: Roseburg Resources - 5/2003 - C.S. File 65/45-32A & M142-36

-----  
Found - 3¼" BLM brass cap on 2½" stainless pipe 0.1 ft. above grade.

Madrone 18" rotten & broken off at ground bears N.50°E., (N.53°30'E.) 10.9 (12.2) ft. (no tag - no paint)

Madrone 26" with 2 tags & no visible scribe or face bears S.71°E., (S.66°E.) 15.8 ft.

Cedar 28" w/tag & healed face bears S.30°E., 43.6 ft

Madrone 23" with NO tag or visible scribe or face bears S.82°W., (S.87°15'W.) 7.7 (6.3) & (9.2) ft.

Distances were measured to side center.

Tag added to 23" madrone.

Trees were paint banded red.

Cedar was also face painted red.

New - D.Fir 12" face scribed "W¼ S4 BT" bears N.1°E., 16.3 ft. Dist. is to spike set at side center, tree paint banded & face painted red. Tag was marked & placed on tree facing corner.

Note - Corner falls approx. 180 ft. south off the southern shoulder of a dead ended east-west dirt spur 300 ± ft. easterly of end of said spur. Corner is on 50-60% SW facing slope. Re-prod to the west is younger (logged 1993±)