

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 302700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Page(s) 7119-20)

-----  
At point of intersection, Set a stone 20x16x10 ins., 12" in the ground, for closing cor. to secs. 32 and 33 marked C C on N. with 4 notches on E. and 2 notches on W. faces; from which  
A Fir 48" dia., bears N.25½°E., 116 lks. dist., mkd. T30S R4W S33 BT.  
A Fir 48" dia., bears N.25°W., 105 lks. dist., mkd. T30S R4W S32 BT.  
A Fir 48" dia., bears S.33 3/4°E., 54 lks. dist., mkd. T30S R4W C C S32 and 33 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - July 1963 - C.S. File 53/26-69

-----  
Found - Stone and all BTs as recorded, except NE. or NW. BTs, now snags.  
Set Brass cap alongside corner stone, mkd:  
County Surveyors Office  
T 30 S R 4 W  
CC 32|33  
T 31 S  
1963  
New BTs -9" R.Fir bears N.33°W., 31.0 ft. scribed CC S32 T30S R4W CS BT.  
8" Laurel bears N.33°E., 31.6 ft. scribed S33 CC T30S R4W CS BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18132)

-----  
The orig. closing cor., perpetuated and recorded by Byron in 1963, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground with 1963 brass cap, from which the remains of the original bearing trees:  
A Fir snag 53" dia., bears N.25½°E., 116 lks. dist., with healed blaze.  
A Fir 45" dia., bears S.33 3/4°E., 54 lks. dist., with healed blaze.  
A decayed Fir stump, size indeterminate bears N.25°W., 105 lks. dist., no marks remain.  
and bearing trees mkd. by Byron:  
A Madrone 10" dia., bears N.31 3/4°E., 49 lks. dist. mkd. CC T30S R4W S33 S BT.  
(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 302700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 17" dia., bears N.33°W., 47 lks. dist., with healed blaze.

Found OK by J. Estabrook, May 2003 - M142-36 & CS65/45-32D

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23843-4)

-----  
The amended closing cor. of secs. 32 & 33, perpetuated by Byron, in 1963; monumented with an iron post, 1¼" dia., firmly set, projecting 11" above ground (alongside of which is the original basalt stone 12x8", firmly set, projecting 7" above ground, mkd. CC on N. face, with 4 notches on east face and 2 notches on west face), with a brass cap (properly) mkd. from which the remains of the original BTs, reported by Rogers, McMullen and Bishop in 1984-86

A decayed fir snag, 36" dia., bears N.25½°E., 76.6 ft., with a healed blaze.

A fir snag, 46" dia., bears S.33¾°E., 35.6 ft., with a healed blaze.

A decayed fir stump, size indeterminate, bears N.25°W., 69.3 ft., no marks visible.

and the BTs mkd. by Byron, reported by Rogers, McMullen, and Bishop in 1984-86

A madrone, 10" dia., bears N.31¾°E., 32.3 ft., with illegible scribe marks visible on partially healed blaze.

A fir, 24" dia., bears N.33°W., 31.0 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., flush with the surface of the ground, with brass cap mkd.

AM  
T30S R4W  
CC  
S32|S33  
S 4  
T31S  
2019

Buried the iron post, 36" long, alongside the stainless steel post.

S.0°24"38"E 7.16 ft

TRUE POINT for the closing cor. of secs. 32 & 33, at intersection with the S. bdy. of the Tp.

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

Continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 302700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T30-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T30S R4W  
CC  
S32|S33  
S 4  
T31S  
2017

from which the bearing trees mkd. by Byron in 1963, for the amended closing cor.

- A madrone, 10" dia., bears N.17¾°E., 38.3 ft., with illegible scribe marks visible on partially healed blaze.
- A fir, 24" dia., bears N.28°W., 36.2 ft., with a healed blaze.