

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 309700

PRIMARY CORNER DESCRIPTION Angle point on No. bdy. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6985)

Set a post at a proper distance cor. of secs. 4, 5, 32 and 33, from which

- A Laurel 12" dia., bears S.80°E., 34 lks. dist.
- A Red Fir 12" dia., bears N.55°E., 20 lks. dist.
- A Red Fir 20" dia., bears N.30°W., 47 lks. dist.
- A Red Fir 30" dia., bears S.65°W., 13 lks. dist.

(NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the Cor. of Tps. 30 and 31 S., R. 5 W., on the offset Meridian Line, - - - -" (V. Laugen, March 1996)

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7021)

A Laurel 8" dia., for cor. to secs. 4, 5, 32 and 33, marked T30S S33 on NE.; R4W S4 on SE.; T31S S5 on SW.; S32 on NW. faces with 4 notches on E. and 2 notches on W. edges, from which

- A Laurel 6" dia., bears N.60½°W., 28 lks. dist. mkd. T30S R4W S32 BT.
- A Maple 4" dia., bears N.6°E., 22 lks. dist. mkd. T30S R4W S33 BT.
- A Laurel 9" dia., bears S.78°E., 23 lks. dist. mkd. T31S R4W S4 BT.
- A Fir 36" dia., bears S.73°W., 28 lks. dist. mkd. T31S R4W S5 BT.

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 17 Pg. 7118 and 7119) and Vol. 18 Page(s) 7844)

(Page 7118)
Bushey fd. and described cor. as set by Thiel)
(Page 7119)
As this is not a cor. to secs. 32 and 33, I destroy the marks on the NE. and NW. faces of tree cor. and also the marks on the witness trees North of this line in T30S R4W.
Page 7844)
The old cor. established for secs. 4, 5, 32 and 33 is not a cor. to secs. 4 and 5. I therefore destroy the marks on the
(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 309700

PRIMARY CORNER DESCRIPTION Angle Point on No. bdy. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

SE. and SW. faces of the tree cor. and the notches on the E. and W. edges and also the marks on the Fir and Laurel witness trees S. of the cor. in T. 31 S R 4 W.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Pages 18131-32)

The Sec. cor. determined at record bearing and distance from the remains of the original bearing trees:

A sawed Fir stump 66" dia., bears S.73°W., 28 lks. dist.;
axe marks visible on opened blaze.

A down, decayed Madrone, size indeterminate, bears
N.60½°W., 28 lks. dist., no marks remain.

This point now becomes an angle point.

At the corner point,

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

AP
T 30 S R 4 W
S 33
S 4
T 31 S
1985

from which new bearing trees

A Fir 13" dia., bears S.24 3/4°E., 31 lks. mkd. AP S4 BT.

A Fir 10" dia., bears N.1°W., 39 lks. mkd. AP S33 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Found OK by J. Estabrook, May 2003 - M142-36 & CS65/45-32E
(New tags were marked & placed on 66" fir stump & 17" fir,
all BTs were band & face painted red.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2872, surveyed April 2017/Oct. 2019- (DCSO records Vol. 59 Page 23833)

The angle point bet. secs 4 & d 33, formerly the original cor. of secs. 4, 5, 32, & 33 on the S. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which the remains of an original BT, reported by Rogers, McMullen and Bishop in 1984-86

A decayed fir stump, 66" dia., bears S.73°W., 18.5 ft.,
with axe marks visible on decayed blaze.

and the BTs mkd. by Rogers, McMullen, and Bishop in 1984-86
continued next page

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 309700

PRIMARY CORNER DESCRIPTION Angle point on No. bdy. Sec. 4

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A fir, 18" dia., bears N.1°E., 25.7 ft., with a healed blaze. (Record, N.1°W.)

A fir, 20" dia., bears S.24¾°E., 20.5 ft., with a healed blaze.