

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Frank Cain - Sept. 21, 1909 - Field Book 10 Page 51 ----- Set post center of sec., from which A Fir 18" bears S.39¼°W., 16½ lks. A Fir 42" dia., bears S.57°E., 61 lks. A Fir 24" dia., bears N.45½°W., 64 lks. A Fir 30" dia., bears N.42½°E., 105 lks.</p>
<p>George J. Wenderoth - 1949 - C.S. File 40/250 B ----- Found old corner set by Cain. Set ½" Iron pipe at corner point. Marked two BTs: 6" Fir S.74°10'W., 133.0 ft. 10" Pine N.8°25'W., 76.7 ft.</p>
<p>BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15499) ----- The center ¼ cor., established and recorded by Cain in 1909, subsequently perpetuated and recorded by Wenderoth in 1949, monumented with an iron pipe, 3/4" dia., firmly set, protruding 2" above ground, from which the remains of a bearing tree mkd. by Cain: A sawed Fir stump 28" dia., bears S.58¼°E., 63 lks. dist., no marks visible. and bearing trees mkd. by Wenderoth: A Fir 15" dia., bears S.73 3/4°W., 201 lks. dist., with healed double blaze. A Ponderosa Pine 19" dia., bears N.8½°W., 116 lks. dist., with healed blaze. At the corner point Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd: C ¼ S 33 1972 from which a new bearing tree: A Fir 7" dia., bears N.67½°W., 6 lks. dist., mkd. C¼ S33 BT.</p>