

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 340240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Sec. Subd. by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15495)

Point for the center ¼ sec. cor. of sec. 28, at intersection with the E. and W. center line of sec. 28.

Set an iron post 28" long 2½" dia., 24" in the ground, with brass cap mkd: C ¼ S 28

1972

from which

A Fir 22" dia., bears N.73°E., 13 lks. dist. mkd. C¼ S28 BT.

A Fir 21" dia., bears S.16°W., 57½ lks. dist. mkd. C¼ S28 BT.

Douglas County Surveyors Office - Larry E. Monrean, Deputy - R.W. Smith; J.M. Powell, crew - Aug. 18/19, 1983 - C.S. File 62/9-25

Found - 1972 BLM brass cap on 2½" iron pipe, firmly set, protrudes 3" above ground. Cap properly marked. 22" now 24" windfall, D.Fir with a well healed blaze, bears N.73°E., 8.6 ft. to root hole.

21" Fir, now a stump disturbed by fire trail construction, bears S.18°W., 38.0 ft. (Rec. S.16°W., 37.8 ft.)

No new monument set.

New BTs- 6 Madrone, double blazed and scribed "C ¼ S28 CS BT", bears S.61°E., 30.8 ft.

5" W.Fir, double blazed and scribed "C ¼ S28 CS BT" bears S.35½°W., 32.9 ft.

9" D.Fir double blazed and scribed "C ¼ S28 CS BT" bears N.19½°E., 65.4 ft.

Monument is located along East edge of fire trail and about 28 ft. West of N-S cutting line, clear cut on East.