

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7840)

Set a stone 14x12x4 ins., 10" in the ground, for ¼ sec. cor. marked ¼ on N. face; from which

A Fir 36" dia., bears S.11°E., 39 lks. dist. mkd. ¼ S BT.

A Fir 10" dia., bears N.75¼°W., 61½ lks. dist. mkd. ¼ S BT

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: George Vaughn; Bill Vaughn - May 20, 1951 - C.S. File 40/232

Determined by O.B.T:

A Fir stump 40" dia., logged, bears S.11°E., 26.0 ft.

At corner point, SET 1" x 30" I.P.

I marked no new trees since Sec. 16 is logged and Sec. 9 is being logged now.

BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1941, surveyed March/Sept. 2000. (DCSO rec. Vol. 53 page(s) 20720)

The ¼ sec. cor. of secs. 9 & 16, perpetuated by Markham in 1951, monumented with an iron pipe, 1" dia., firmly set, projecting 6 ins. above ground, and a basalt stone, 8 x 11 x 3", mkd. 1/4, lying loose alongside, from which the remains of an original bearing tree

A sawed fir stump, 44" dia., bears S.7¾°E., 26.2 ft., with scribe marks ¼ S visible on opened blaze. (Rec., S.11°E., 25.7 ft.)

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, in a collar of stone, with brass cap mkd.

T 31 S R 4 W

¼ 9

 S 16

 2000

from which

A hemlock, 14" dia., bears N.2°E., 2.4 ft., mkd. ¼ S9 BT.

A hemlock, 26" dia. bears S.33°W., 15.2 ft., mkd. ¼ S16 BT

Each new bearing tree has a 2½"X ¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.

Deposit a magnet in a white plastic case at the base, the iron pipe inside and bury the original stone alongside, the stainless steel post.