

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6985)

Set ¼ sec. post at proper distance, from which
A chinquapin, 6" dia., bears S.2°E., 24 lks.
A Laurel, 4" dia., bears N.45°E., 26 lks.

GLO survey by Wm. Thiel under contract 535 dated Feb. 5, 1889 - (DCSO records Vol. 17 Page(s) 7020)

Set a fir post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor. marked ¼ S on N face, from which
A fir, 9" dia., bears S.80¼°W., 27 lks., mkd: ¼ S BT.
A fir, 48" dia., bears N.43°W., 21 lks., mkd: ¼ S BT.

Fd. & used on GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7844)

Jerry Estabrook - For: Roseburg Resources - 5/2003 - C.S. File 65/45-32I & M142-36

Set - 2½" Alum. cap on a 5/8"x30" iron rod 29" deep. Set at proportioned dist. between closing corners sec. 4 on township line T30S - T31S between angle points.
Marked: T30S R4W

	¼	S4
	T31S	R4W
	2003	
	LS	2703

D.Fir 16" bears N.61°E., 54.6 ft. face scribed "T30S R4W BT"
D.Fir 20" bears S.45°E., 27.7 ft. face scribed "T31S R4W S4 N¼ BT"
D.Fir 25" bears S.65°W., 84.7 ft. face scribed "T31S R4W S4 N¼ BT"
D.Fir 11" bears N.32°W., 47.8 ft. face scribed "T30S R4W BT"

Distances are to spike set at side center. Trees were paint banded & face painted red. Tags were filled out & placed on BTs facing corner.

Note- Falls in a 25 ± ft. wide draw 15 ft. east of a 3 ft. wide northerly flowing creek. Slopes to east & west are 70-80%