

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 348700

PRIMARY CORNER DESCRIPTION Angle point on No. Bdy. Sec. 4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 16 Page(s) 6985)

-----  
Set ¼ sec. post at proper distance, from which  
A Chinquapin 6" dia., bears S.2°E., 24 lks. dist.  
A Laurel 4" dia., bears N.45°E., 26 lks. dist.

*(NOTE: The above corner by Ford must be in doubt due to statement by Thiel in Vol. 17 Pg. 7024 - "In order to be sure that Deputy Ford did not run the South Bdy. of this Tp. and set any Cors., I went to the Cor. of Tps. 30 and 31 S., R. 5 W., on the offset Meridian Line, - - - -" (V. Laugen, March 1996)*

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7020)

-----  
Set a Fir post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S on N. face, from which  
A Fir 9" dia., bears S.80¼°W., 27 lks. dist. mkd. ¼ S BT.  
A Fir 48" dia., bears N.43°W., 21 lks. dist. mkd. ¼ S BT.

GLO survey by Bushey in 1893, tied and described Thiel corner. (DCSO records, Vol. 17 Page 7119)

Jerry Estabrook - For: Roseburg Resources - 5/2003 - C.S. File 65/45-32J & M142-36

-----  
Looked for not found.