

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7788)

-----  
Set ¼ sec. post, from which  
A Maple 24" dia., bears N.75°W., 28 lks. dist.  
A Maple 5" dia., bears S.80°E., 15 lks. dist.

Douglas Co. Surveyors Office - George Wenderoth, Deputy - Dec. 1947 - C.S. File 40/29 and M 4-75

-----  
Set 1" I.Pipe, 8" below surface of field, halfway between sec. corner.  
Marked - 30" Cedar bearing N.8°07'W., 211.1 ft. dist.  
14" Ash bearing N.85°20'E., 177.5 ft. dist.

Douglas County Surveyors Office - James Byron - For: Douglas County, Cow Creek Rd. #36 - Jan. 8, 1957 - Road File drawer 48/Rd. 36

-----  
Found - 14" Ash as renewed by Wenderoth, N.85°20'E., 177.5 ft., good condition.  
The 30" Cedar N.8°07'W., is gone.  
Also found 1" I.P., 8" under.  
Blazed and scribed:  
6.3 ft. W.Oak, N.34½°W., 408.0 ft. "¼ S28 CS BT"

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Feb. 1966 - C.S. File 54/20-10

-----  
Found - Iron pipe, 8" underground.  
6.3 ft. W.oak N.34½°W., 408.0 ft., good condition, scribe visible.  
14" Ash, N.85°20'E., 177.5 ft., scribe visible "¼ CS BT". (Creek bank badly washed, probably lose this tree)  
New BT - D.Fir S.69°E., 508.5 ft. scribed "¼ S27 CS BT"  
Power pole #E1510, West 20.3 ft.

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #778, surveyed July/Sept. 1972- (DCSO records Vol. 38 Page(s) 15477)

-----  
The ¼ sec. cor., reestablished and recorded based on proportionate method by Wenderoth in 1947, monumented with an iron pipe, 1" dia., firmly set, the top 8" below the surface of the ground, from which a bearing tree mkd. by Wenderoth:  
(Cont. Next Page)

TOWNSHIP 31 RANGE 04 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

An Ash 18" dia., bears N.84°E., 271 lks. dist., with scribe marks ¼ C BT visible on partially healed double blaze.

and a bearing tree mkd. by Byron in 1956:

A triple Maple 72" dia., bears N.36¼°W., 618 lks. dist., with scribe marks CS BT S28 visible on partially healed double blaze.

and a bearing tree and bearing object mkd. by the County in 1966:

A Fir 28" dia., bears S.68½°E., 770 lks. dist. mkd. with healed double blaze.

A power pole, Number E 1510 bears N.89 3/4°W., 30½ lks. dist.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., the top 8" below the surface of the ground, and directly over iron pipe, with brass cap mkd:

T 31 S R 4 W

¼  
S 28 | S 27  
1972

3/20/2007 placed \* after number because corner is under water in Galesville Dam